

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020 Page 1 of 12

Revision date: 12.30.2021

Absco Swedish Finish Retarder

SECTION 1: Identification

Product Identifier

Product Name: Absco Swedish Finish Retarder

Product code: PR163068

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Finishes, Coatings, and Related Materials

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer: United States

Canlak Coatings 1999 Elizabeth Street North Brunswick, New Jersey 089026316 (732)821-3200 https://canlakcoatings.com

Emergency Telephone Number:

United States

CHEMTREC (703)527-3887 (24 HRS) (800)424-9300

SECTION 2: Hazard(s) Identification

GHS Classification:

Serious eye damage, category 1 Flammable liquids, category 3

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Label elements

Hazard Pictograms:







Signal Word: Danger **Hazard statements:**

H226 Flammable liquid and vapor H318 Causes serious eye damage H335 May cause respiratory irritation

Precautionary Statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P271 Use only outdoors or in a well-ventilated area

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER/doctor/...

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use ... to extinguish

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312 Call a POISON CENTER/doctor/.../if you feel unwell

P403+P235 Store in a well-ventilated place. Keep cool

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P405 Store locked up

P501 Dispose of contents/container to...

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 34590-94-8	(2-Methoxymethylethoxy)propanol	<95
CAS Number: 71-36-3	n-Butanol	<15

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Page 2 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Product is flammable. Exposure to sources of ignition may cause physical injury.

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

If respiratory symptoms persist, seek medical attention.

Skin/eye burns require immediate treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, CO2, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Page 3 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020 Page 4 of 12

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	n-Butanol	71-36-3	TLV-TWA: 20 ppm (8-Hour Exposure Limit)
	(2-Methoxymethylethoxy)propanol	34590-94-8	8-Hour TWA: 100 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	15-Minute STEL: 150 ppm
NIOSH	n-Butanol	71-36-3	Ceiling Limit: 50 ppm (150 mg/m³)
	n-Butanol	71-36-3	IDLH: 1400 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	IDLH: 600 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	15-Minute STEL: 900 mg/m³ (150 ppm)
	(2-Methoxymethylethoxy)propanol	34590-94-8	REL-TWA: 600 mg/m³ (100 ppm [up to 10 hr])
OSHA	n-Butanol	71-36-3	8-Hour TWA-PEL: 100 ppm (300 mg/m ³)
	n-Butanol	71-36-3	Ceiling Limit: 50 ppm (150 mg/m³)
	(2-Methoxymethylethoxy)propanol	34590-94-8	8-Hour TWA-PEL: 600 mg/m³ (100 ppm)
	(2-Methoxymethylethoxy)propanol	34590-94-8	15-Minute STEL: 900 mg/m³ (150 ppm)
United States(California)	n-Butanol	71-36-3	Ceiling Limit: 50 ppm (150 mg/m3)
	(2-Methoxymethylethoxy)propanol	34590-94-8	15-Minute STEL: 900 mg/m³ (150 ppm)
	(2-Methoxymethylethoxy)propanol	34590-94-8	8-Hour TWA-PEL: 600 mg/m³ (100 ppm)

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Page 5 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020 Pa

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Personal Protection Equipment

Eye and Face Protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Clear liquid
Odor	Alcohol-like
Odor threshold	N/A
рН	N/A
Melting point/freezing point	N/A
Initial boiling point/range	118°C
Flash point (closed cup)	36°C
Evaporation rate	N/A
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	1.5%

Page 6 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Vapor pressure	N/A
<u> </u>	
Vapor density	N/A
Density	0.89 +/- 0.02 g/cc
Relative density	0.89 +/- 0.02
Solubilities	N/A
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials. Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
n-Butanol	oral	LD50 Rat: 790 mg/kg
	dermal	LD50 Rabbit: 3400 mg/kg
(2-		LD50 Rat: 5180 mg/kg
Methoxymethylethoxy)propano	dermal	LD50 Rabbit: 9510 mg/kg

Skin Corrosion/Irritation

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Page 7 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Substance Data:

Name	Result
n-Butanol	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
n-Butanol	Causes serious eye damage.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available. **Substance Data:** No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
n-Butanol	Not Applicable
(2- Methoxymethylethoxy)propano I	Not Applicable

National Toxicology Program (NTP):

Name	Classification
n-Butanol	Not Applicable
(2- Methoxymethylethoxy)propano I	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Page 8 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Assessment:

May cause respiratory irritation.

Product Data: No data available. Substance Data:

Name Result n-Butanol May cause drowsiness or dizziness May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available. **Other Information:**No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result	
n-Butanol	Aquatic Plants EC50 Green algae: 225 mg/L (96 Hours)	
	Aquatic Invertebrates EC50 Daphnia magna: 1328 mg/L (48 Hours)	
	Fish LC50 Pimephales promelas: 1376 mg/L (96 Hours)	
(2-	Aquatic Plants EC50 Freshwater green algea: >969 mg/L (72 hr)	
Methoxymethylethoxy)propand	Fish LC50 Pimephales promelas: >10,000 mg/L (96 hr)	

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
n-Butanol	Aquatic Invertebrates NOEC Daphnia magna: 4.1 mg/L (21 Days)

Persistence and Degradability

Product Data: No data available.

Substance Data:

Page 9 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Name	Result
n-Butanol	The substance is readily biodegradable (> 92% degradation in 28 days).
(2- Methoxymethylethoxy)propano	Readily biodegradable (79% degradation in 28 days).

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result	
n-Butanol	The substance is not expected to bioaccumulate (BCF: 3.16 L/Kg).	
(2- Methoxymethylethoxy)propano	The substance is not expected to bioaccumulate (Log Kow: -0.350).	

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
n-Butanol	The substance is highly mobile (Log Koc: 0.54).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

n-Butanol	The substance is not PBT.
(2- Methoxymethylethoxy)propan ol	The substance is not PBT.

vPvB assessment:

n-Butanol	The substance is not vPvB.
(2- Methoxymethylethoxy)propan	The substance is not vPvB.
01	

Other Adverse Effects:

Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage.

SECTION 13: Disposal Considerations

Disposal Methods:

Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:

Page 10 of 12

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Page 11 of 12

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	UN1263, Flammable
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	UN1263
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	UN1263
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed. **Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

	71-36-3	n-Butanol		Listed
CEI	CERCLA:			
	71-36-3	n-Butanol	Listed	5000
RC	RCRA:			
	71-36-3	n-Butanol	Listed	U031

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

71-36-3	In-Butanol	Listed
1	11 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 -	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Absco Swedish Finish Retarder

34590-94-8	(2-Methoxymethylethoxy)propanol	Listed
lew Jersey Right	to Know:	•
71-36-3	n-Butanol	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed
lew York Right to	Know:	·
71-36-3	n-Butanol	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed
ennsylvania Righ	nt to Know:	·
71-36-3	n-Butanol	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Canlak Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Canlak Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-3-1 **HMIS:** 2*-3-1

Initial Preparation Date: 06.16.2020

Revision date: 12.30.2021

Revision Notes:

Revision Date	Notes
2020-06-16	Version 01
2021-12-30	Version 02

End of Safety Data Sheet

Page 12 of 12