

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 1 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

SECTION 1: Identification

Product identifier

Product name: Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

Product code: GRMCS1, GRMCS4, GRMCS5

Recommended use of the product and restriction on use

Relevant identified uses: Finishes, Coatings, and Related Materials

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

Absolute Coatings
1999 Elizabeth Street
North Brunswick , New Jersey 089026316
(732)821-3200

Emergency telephone number:

United States

CHEMTREC
(703)527-3887 (24 HRS)
(800)424-9300

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2
Eye irritation, category 2A
Flammable liquids, category 3
Germ cell mutagenicity, category 1B
Carcinogenicity, category 1B

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor
H315 Causes skin irritation
H319 Causes serious eye irritation
H340 May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H350 May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 2 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

Precautionary statements:

- P264 Wash skin thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P302+P352 IF ON SKIN: Wash with plenty of water/ ...
- P321 Specific treatment (see ... on this label)
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P362 Take off contaminated clothing and wash it before reuse
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P337+P313 If eye irritation persists: Get medical advice/attention
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P370+P378 In case of fire: Use ... to extinguish
- P308+P313 IF exposed or concerned: Get medical advice/attention
- P403+P235 Store in a well-ventilated place. Keep cool
- P405 Store locked up
- P501 Dispose of contents/container to...

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 1330-20-7	Xylene	<10
CAS number: 98-56-6	4-Chloro- α,α,α -trifluorotoluene	<30
CAS number: 108-65-6	1-Methoxy-2-propanol acetate	<10
CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	<20
CAS number: 540-88-5	tert-butyl acetate	<10

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 3 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Exposure may cause genetic defects.

Exposure may cause cancer.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 4 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions.

Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental precautions:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 5 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Xylene	1330-20-7	TWA: 100 ppm
	Xylene	1330-20-7	STEL: 150 ppm
	tert-butyl acetate	540-88-5	8-Hour TWA: 50 ppm
	tert-butyl acetate	540-88-5	15-Minute STEL: 150 ppm
OSHA	Xylene	1330-20-7	8-Hour TWA-PEL: 435 mg/m ³
	Xylene	1330-20-7	8-Hour TWA-PEL: 100 ppm

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 6 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Xylene	1330-20-7	STEL: 150 ppm
	Xylene	1330-20-7	STEL: 655 mg/m ³
	tert-butyl acetate	540-88-5	8-Hour TWA-PEL: 200 ppm
	tert-butyl acetate	540-88-5	8-Hour TWA-PEL: 950 mg/m ³
NIOSH	Xylene	1330-20-7	REL-TWA: 435 mg/m ³
	Xylene	1330-20-7	REL-TWA: 100 ppm
	Xylene	1330-20-7	STEL: 655 mg/m ³
	Xylene	1330-20-7	STEL: 150 ppm
	tert-butyl acetate	540-88-5	TWA: 200 ppm (REL - (up to a 10 hour work day))
	tert-butyl acetate	540-88-5	TWA: 950 mg/m ³ (REL - (up to a 10 hour work day))
	tert-butyl acetate	540-88-5	IDLH: 1500 ppm
United States(California)	Xylene	1330-20-7	8-Hour TWA-PEL: 100 ppm
	Xylene	1330-20-7	PEL-STEL: 150 ppm (15- minute)
	Xylene	1330-20-7	PEL Ceiling: 300 ppm
	tert-butyl acetate	540-88-5	8-Hour TWA-PEL: 200 ppm (OSHA (California))
	tert-butyl acetate	540-88-5	8-Hour TWA-PEL: 950 mg/m ³ (OSHA (California))
	1-Methoxy-2-propanol acetate	108-65-6	15-Minute STEL: 811 mg/m ³ (150 ppm)
	1-Methoxy-2-propanol acetate	108-65-6	8-Hour TWA-PEL: 541 mg/m ³ (100 ppm)
WEEL	1-Methoxy-2-propanol acetate	108-65-6	TWA: 50 ppm

Biological limit values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
United States	Xylene	1330-20-7	Methylhippuric acids		End of shift	1.5 g/g

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 7 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Hazy liquid
Odor	Aromatic
Odor threshold	N/A
pH	N/A
Melting point/freezing point	N/A
Initial boiling point/range	N/A
Flash point (closed cup)	27.2°C
Evaporation rate	Slower than diethyl ether
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	N/A
Vapor pressure	N/A
Vapor density	Heavier than air
Density	1.08 +/- 0.02 g/cc
Relative density	1.08 +/- 0.02
Solubilities	Slightly soluble in water.
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

Other information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 8 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Xylene	dermal	LD50 Rabbit: 1700 mg/kg
	inhalation	LC50 Rat: 5000 ppmV (4 h)
	oral	LD50 Mouse: 5251 mg/kg
4-Chloro- α,α,α -trifluorotoluene	oral	LD50 Rat: 5546 mg/kg
	inhalation	LC50 Rat: > 32.03 mg/L (4 hrs)
1-Methoxy-2-propanol acetate	oral	LD50 Rat: 5155 mg/kg
	dermal	LD50 Rabbit: >5000 mg/kg
tert-butyl acetate	dermal	LD50 rabbit: > 2000 mg/kg
	oral	LD50 rat: 4100 mg/kg
	inhalation	LC50 rat: >2.23 mg/L (4 hour)

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Substance data:

Name	Result
Xylene	Causes skin irritation.
4-Chloro- α,α,α -trifluorotoluene	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye irritation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 9 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

Product data:

No data available.

Substance data:

Name	Result
4-Chloro- α,α,α -trifluorotoluene	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment:

May cause cancer.

Product data: No data available.

Substance data:

Name	Species	Result
Solvent naphtha (petroleum), light arom.	Not applicable.	Component may cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Xylene	Group 3
Solvent naphtha (petroleum), light arom.	Not Applicable
1-Methoxy-2-propanol acetate	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Xylene	Not Applicable
Solvent naphtha (petroleum), light arom.	Not Applicable
1-Methoxy-2-propanol acetate	Not Applicable

OSHA Carcinogens: Not applicable

Germ cell mutagenicity

Assessment:

May cause genetic defects.

Product data:

No data available.

Substance data:

Name	Result
Solvent naphtha (petroleum), light arom.	May cause genetic defects.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 10 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
4-Chloro- α,α,α -trifluorotoluene	Component affects the respiratory system.
1-Methoxy-2-propanol acetate	May cause dizziness or drowsiness.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Solvent naphtha (petroleum), light arom.	May be fatal if swallowed and enters airways.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
4-Chloro- α,α,α -trifluorotoluene	EC50 Green Algae: ≥ 0.41 mg/L (72 hrs)
	LC50 Daphnia magna: 2 mg/L (48 hrs)
	LC50 Rainbow Trout: 3 mg/L (96 hrs)
1-Methoxy-2-propanol acetate	LC50 Pimephales promelas: 130 mg/L (96 hours)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 11 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

Name	Result
1-Methoxy-2-propanol acetate	NOEC Oryzias latipes: 47.5 mg/L (14 days)

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Xylene	Readily biodegradable in water.
4-Chloro- α,α,α -trifluorotoluene	Not readily biodegradable. (28 d) 19.2%
1-Methoxy-2-propanol acetate	Readily biodegradable.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Xylene	BCF: >8.1 - <25.9
1-Methoxy-2-propanol acetate	Log Kow: 1.2

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
Xylene	Moderately Mobile (Log Koc: 2.73)

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT..

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB..

Substance data:

PBT assessment:

1-Methoxy-2-propanol acetate	Substance is not PBT.
------------------------------	-----------------------

vPvB assessment:

1-Methoxy-2-propanol acetate	Substance is not vPvB.
------------------------------	------------------------

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	UN1263
UN proper shipping name	Paint


Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 05.13.2020

Page 12 of 14


Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

UN transport hazard class(es)	3	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	

International Maritime Dangerous Goods (IMDG)

UN number	UN1263	
UN proper shipping name	Paint	
UN transport hazard class(es)	3	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN1263	
UN proper shipping name	Paint	
UN transport hazard class(es)	3	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

1330-20-7	Xylene	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Listed
108-65-6	1-Methoxy-2-propanol acetate	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
540-88-5	tert-butyl acetate	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b):

1330-20-7	Xylene	Not Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 13 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

540-88-5	tert-butyl acetate	Not Listed
----------	--------------------	------------

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals:

1330-20-7	Xylene	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Not Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
540-88-5	tert-butyl acetate	Not Listed

CERCLA:

1330-20-7	Xylene	Listed	100 lb
540-88-5	tert-butyl acetate	Listed	5000

RCRA:

1330-20-7	Xylene	Listed	U239
-----------	--------	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

1330-20-7	Xylene	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Not Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
540-88-5	tert-butyl acetate	Listed

New Jersey Right to Know:

1330-20-7	Xylene	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
540-88-5	tert-butyl acetate	Listed

New York Right to Know:

1330-20-7	Xylene	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
540-88-5	tert-butyl acetate	Listed

Pennsylvania Right to Know:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 14 of 14

Classic World Moisture Cure Crystal Clear Finish Satin 350 VOC

1330-20-7	Xylene	Listed
98-56-6	4-Chloro- α,α,α -trifluorotoluene	Not Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
540-88-5	tert-butyl acetate	Listed

California Proposition 65:

⚠️WARNING: This product can expose you to 4-Chloro- α,α,α -trifluorotoluene; which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-3-0

HMIS: 3*-3-0

Initial preparation date: 05.13.2020

Revision Notes:

Revision Date	Notes
2020-04-30	Version 02

End of Safety Data Sheet