

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 1 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

SECTION 1: Identification

Product Identifier

Product Name: Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

Product code: SC02092401, SC02092404, SC02092405

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Finishes, Coatings, and Related Materials

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Canlak Coatings
1999 Elizabeth Street
North Brunswick, New Jersey 089026316
(732)821-3200
<https://canlakcoatings.com>

Emergency Telephone Number:

United States

CHEMTREC
(703)527-3887 (24 HRS)
(800)424-9300

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin irritation, category 2

Eye irritation, category 2A

Flammable liquids, category 3

Specific target organ toxicity - repeated exposure, category 1

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H226 Flammable liquid and vapor

H315 Causes skin irritation

H319 Causes serious eye irritation

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 2 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

H372 Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Precautionary Statements:

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P321 Specific treatment (see ... on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use ... to extinguish

P314 Get medical advice/attention if you feel unwell

P403+P235 Store in a well-ventilated place. Keep cool

P501 Dispose of contents/container to...

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 8052-41-3	Stoddard Solvent with < 0.1% Benzene content	<30
CAS Number: 64742-47-8	Distillates (petroleum), hydrotreated light	<30
CAS Number: 93-58-3	Methyl benzoate	<0.1

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 3 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Product is flammable. Exposure to sources of ignition may cause physical injury.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Causes damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

Skin/eye burns require immediate treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 4 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 5 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	PEL: 525 mg/m ³
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	PEL: 100 ppm
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 2000 mg/m ³ (500 ppm [aliphatic hydrocarbons])
NIOSH	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	Ceiling Limit: 1800 mg/m ³ (15-min)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	IDLH: 20000 mg/m ³
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	REL: 350 mg/m ³
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 350 mg/m ³ (up to 10 hr [petroleum distillates, naphtha])
	Distillates (petroleum), hydrotreated light	64742-47-8	Ceiling Limit: 1800 mg/m ³ ([15 min] petroleum distillates, naphtha)
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 100 mg/m ³ (up to 10 hr [kerosene])
ACGIH	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 100 ppm
	Distillates (petroleum), hydrotreated light	64742-47-8	TLV-TWA: 200 mg/m ³ (Kerosene and jet-fuels [non-aerosol], as total hydrocarbon vapor)
United States(California)	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 100 ppm
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 525 mg/m ³
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 1600 mg/m ³ (400 ppm [aliphatic hydrocarbons])

Biological Limit Values:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 6 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Amber liquid
Odor	Mild
Odor threshold	N/A
pH	N/A
Melting point/freezing point	N/A
Initial boiling point/range	161-198°C
Flash point (closed cup)	> 38°C
Evaporation rate	N/A
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	0.7%
Vapor pressure	N/A
Vapor density	Heavier than air
Density	0.89 +/- .02 g/cc
Relative density	0.89 +/- .02

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 7 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

Solubilities	N/A
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Distillates (petroleum), hydrotreated light	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5.28 mg/L (4 hr [vapor])
Methyl benzoate	oral	LD50 Rat: 1177 mg/kg
	dermal	LD50 Rat: >5000 mg/kg
Stoddard Solvent with < 0.1% Benzene content	oral	LD50 Rat: > 5000 mg/kg
	inhalation	LC50 Rat: > 5.5 mg/L (4 h)
	dermal	LD50 Rabbit: >3000 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 8 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

No data available.

Substance Data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Distillates (petroleum), hydrotreated light	Not Applicable
Stoddard Solvent with < 0.1% Benzene content	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Distillates (petroleum), hydrotreated light	Not Applicable
Stoddard Solvent with < 0.1% Benzene content	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 9 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment:

Causes damage to organs through prolonged or repeated exposure.

Product Data:

No data available.

Substance Data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes damage to the Central Nervous System through prolonged or repeated exposure via inhalation.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.
Stoddard Solvent with < 0.1% Benzene content	May be fatal if swallowed and enters airways.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Fish LC50 <i>Lepomis macrochirus</i> : 2.2 mg/L (96 hr)
	Aquatic Invertebrates EC50 <i>Daphnia magna</i> : 1.4 mg/L (48 hr)
	Aquatic Plants EC50 <i>Pseudokirchneriella subcapitata</i> : 6.7 mg/L (72 hr)
Methyl benzoate	Fish LC50 <i>Danio rerio</i> : 23 mg/L (96 hours)
	Aquatic Invertebrates EC50 <i>Daphnia magna</i> : 28.5 mg/L (48 hours)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 10 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Fish LC50 Oncorhynchus mykiss: 0.14 mg/L (96 hours)

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Fish NOEC Oncorhynchus mykiss: 0.02 mg/L (30 d)
Distillates (petroleum), hydrotreated light	Aquatic Invertebrates EC50 Daphnia magna: 0.81 mg/L (21 d)

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Methyl benzoate	Readily biodegradable.
Stoddard Solvent with < 0.1% Benzene content	Readily biodegradable.
Distillates (petroleum), hydrotreated light	Substance is considered to be inherently biodegradable in water.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	BCF: 39.66 L/Kg ww; Not considered to be bioaccumulative.
Distillates (petroleum), hydrotreated light	This substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Methyl benzoate	Koc at 20°C: 178
Stoddard Solvent with < 0.1% Benzene content	Koc at 20°C: 1451
Distillates (petroleum), hydrotreated light	This substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 11 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

Methyl benzoate	Substance is not PBT.
Stoddard Solvent with < 0.1% Benzene content	The substance is not PBT.
Distillates (petroleum), hydrotreated light	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as PBT at concentrations above 0.1%.

vPvB assessment:

Methyl benzoate	Substance is not vPvB.
Stoddard Solvent with < 0.1% Benzene content	The substance is not vPvB.
Distillates (petroleum), hydrotreated light	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as vPvB at concentrations above 0.1%.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:


Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:


Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	UN 1263, Combustible, No red label required
UN Proper Shipping Name	Paint
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	UN1263
UN Proper Shipping Name	Paint
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	UN1263
-----------	--------

Safety Data Sheet


According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 12 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

UN Proper Shipping Name	Paint
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	100 lb
------------	---	--------	--------

RCRA:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	D001
------------	---	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed

New Jersey Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
93-58-3	Methyl benzoate	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed

New York Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
93-58-3	Methyl benzoate	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed

Pennsylvania Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Canlak Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally,

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.12.2020

Page 13 of 13

Revision date: 01.04.2022

Sampson Poly-U-Var Premium Urethane Wood Finish Gloss

Canlak Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 1-2-1

HMIS: 1*-2-1

Initial Preparation Date: 05.12.2020

Revision date: 01.04.2022

Revision Notes:

Revision Date	Notes
2020-05-11	Version 02
2022-01-04	Version 03

End of Safety Data Sheet