



GRAND CLEAR 1K WOOD FLOOR FINISH



SPECIFICATIONS:

VOC	<275 g/L
Solids	28% - 32%
Flash Point.....	> 212°F (> 100°C)
Solvent	Water
Viscosity.....	40-80 cps
Odor	Low Odor
Coverage.....	500 sq. ft/gal
Dry Time:.....	2 - 4 Hours
Color (Wet).....	Slightly Milky
Color (Dry).....	Clear
Sheens.....	Gloss, Semi-Gloss, Satin, Matte
Sizes	1g & 5g Containers

FEATURES

- Crystal-Clear Non-Yellowing Finish
- Easy To Apply, Water Clean-Up, Scuff Resistant
- Advanced Resin Technology With No Catalyst Or X-Linker
For Excellent Adhesion, Flow, Leveling and Flexibility

THE NEWEST GENERATION OF WATER CLEANUP WOOD FLOOR FINISHES FOR PROFESSIONALS

Absco Grand 1K Wood Floor Finish is a crystal-clear non-yellowing finish that offers the newest Advanced Resin Technology with no catalyst or X-linker for excellent adhesion, flow, leveling and flexibility. The easy to apply formula is water cleanup and scuff resistant.

Please refer to the product label for specific surface preparation and application instructions.



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit canlakcoatings.com or call us at **800-432-4333**.



GRAND CLEAR 1K

WOOD FLOOR FINISH

PREPARATION:

For new floors, abrade seal coat and tack with water.

For screen and coats, clean floor and then screen thoroughly with new 150 grit. Vacuum and tack with water (no mineral spirits).

APPLICATION:

Eliminate direct air drafts on floor during application. Apply with a light weight T-bar @ 450-500 sf/gal. Increase airflow when film has become tack free. Wait 4-6 hours before next coat (under normal conditions: 65-80°F and 40-60% RH). High humidity and cooler temperatures may extend dry times. If more than 15 hours have elapsed between coats, the floor must be abraded with a SPP pad before next coat. Generally, one coat of stain or sealer and two coats of Clear 1K will provide adequate protection for new floors. However, use your professional discretion to achieve desired results.

MAINTENANCE and CLEANUP: For daily cleaning, dust mop with Craftsman's Choice Hardwood Floor Cleaner. Follow directions that accompany the cleaner. Tools may be cleaned with water.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRECAUTIONARY STATEMENTS**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

WARNING. Causes skin irritation, Causes serious eye irritation. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not breathe vapors, spray mist, dust or chips from sanding. Avoid contact with skin, eyes or clothing. While spraying paint, or sanding surface, wear a mask or pesticide respirator approved by the National Institute for Occupational Safety and Health. Wear protective clothing (long sleeved cotton shirt, long pants, hat, gloves (such as nitril or butyl). Shoes and socks. Wash thoroughly with soap and water after handling and before eating, drinking, using tobacco or using the toilet. Remove contaminated clothing and wash before reuse. Use in well-ventilated area.

Follow manufacturers instructions for cleaning/maintaining Personal Protection Equipment (PPE). If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advices.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Never give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately; wash with soap and water. Rinse with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec - 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

PHYSICAL AND CHEMICAL HAZARDS (STORAGE)

Store locked up and well-ventilated area.

KEEP FROM FREEZING. DO NOT THIN.

Spill: Absorb with inert and dispose of as specified under "Clean Up".

Clean Up: Soap and Water.

Disposal: Empty containers may retain residue. Follow label warnings even after the container is emptied. To dispose of contaminated absorbent, container and unused contents contact your sanitation department or State-designated environmental agency.

Refer to Safety Data Sheet for additional health and safety information.

KEEP OUT OF REACH OF CHILDREN

INGREDIENTS: 1-Methoxy-2-propanol (107-98-2), Water (7732-18-5), Tris(2-Butoxyethyl)phosphate (78-51-3), 2-Butoxyethanol (111-76-2).

FACTORS BEYOND OUR CONTROL PREVENT US FROM ASSUMING RESPONSIBILITY FOR DAMAGE TO PROPERTY OR PERSON, EVEN WHEN THIS PRODUCT IS APPLIED ACCORDING TO DIRECTIONS. IN NO EVENT SHALL OUR LIABILITY EXCEED THE PURCHASE PRICE HEREOF.

THIS PRODUCT HAS A MAXIMUM VOC OF 275 G/L.

FOR WOOD SUBSTRATES ONLY.

Item Number	Description	Size	Number per Case	Weight per Case
96001	Absco Grand Clear 1K - Gloss	GL	4	48 lbs.
96005	Absco Grand Clear 1K - Gloss	5G	N/A	38 lbs.
96101	Absco Grand Clear 1K - Satin	GL	4	48 lbs.
96105	Absco Grand Clear 1K - Satin	5G	N/A	38 lbs.
96201	Absco Grand Clear 1K - Semi-Gloss	GL	4	48 lbs.
96205	Absco Grand Clear 1K - Semi-Gloss	5G	N/A	38 lbs.
96301	Absco Grand Clear 1K - Matte	GL	4	48 lbs.
96305	Absco Grand Clear 1K - Matte	5G	N/A	38 lbs.



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit canlakcoatings.com or call us at **800-432-4333**.