



# SOLO PRO CLEAR WOOD FLOOR FINISH



## SPECIFICATIONS:

VOC .....	275 g/L
Solids .....	30% (+/- 1% varies by sheen)
Flash Point .....	>100° C or >212° F
Solvent .....	Water
Viscosity .....	40 - 80 cps (60 - 100 for Matte)
Odor .....	Low Odor
Coverage .....	500 - 600 sq. ft/gal (Varies with Surface Porosity)
Dry Time .....	1 - 3 Hours
Color .....	Milky (When Wet)
Sheens .....	Satin & Matte
Sizes .....	1g & 5g Containers

## FEATURES

- Easy Application
- Roller & T-Bar Application
- Crystal Clear / Non-Yellowing
- Low Odor and Low VOC
- Good Build and Film Clarity When Dry

## A CRYSTAL CLEAR, FAST-DRYING WOOD FINISH THAT'S EASY TO USE

ABSCO SOLO PRO CLEAR Wood Floor Finish is a non-yellowing waterborne urethane finish. It is easy to apply and abrade while providing very good adhesion with rapid dry times, allowing for multiple coats in one day to get the job done faster. Solo Pro Clear can be used as a base and topcoat delivering a durable finish that is scuff-and-chemical resistant. Solo Pro Clear includes all the key elements for treating and protecting wooden floors from start to finish!

**Please refer to the product label for specific surface preparation and application instructions.**



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit [canlakcoatings.com](http://canlakcoatings.com) or call us at **800-432-4333**.



# SOLO PRO CLEAR WOOD FLOOR FINISH

**ABSOCO SOLO PRO CLEAR Wood Floor Finish is a non-yellowing waterborne urethane finish. It is easy to apply and abrade while providing very good adhesion with rapid dry times, allowing for multiple coats in one day to get the job done faster. Solo Pro Clear can be used as a base and topcoat delivering a durable finish that is scuff-and-chemical resistant. Solo Pro Clear includes all the key elements for treating and protecting wooden floors from start to finish!**

#### PREPARATION:

For new floors, abrade seal coat and tack with water.

For screen and coats, clean floor and then screen thoroughly with new 150 grit. Vacuum and tack with water (no mineral spirits).

#### APPLICATION:

Eliminate direct air drafts on floor during application. Apply with a light weight T-bar @ 450-500 sf/gal. Increase airflow when film has become tack free. Wait 1-3 hours before next coat (under normal conditions: 65-80°F and 40-60% RH). High humidity and cooler temperatures may extend dry times. If more than 15 hours have elapsed between coats, the floor must be abraded with a SPP pad before next coat. Generally, we recommend one coat of either stain or sealer and two coats of Absco Platinum 2K to provide adequate protection for new wood floors. However, use your professional discretion to achieve desired results.

#### Re-Coating Procedures For Previously Sealed or Finished Wood Floors

1. All wax, grease, soaps and dirt must be removed thoroughly.
2. Screen lightly with a SPP pad between coats of polyurethane.
3. Vacuum up all dust possible then tack floor with a clean dampened towel.
4. Apply MINIMUM of two coats of polyurethane finish in the manner described above.

**MAINTENANCE and CLEANUP:** For daily cleaning, dust mop with Craftsman's Choice Hardwood Floor Cleaner. Follow directions that accompany the cleaner. Tools may be cleaned with water.

**WARNING!** IF YOU SCRAPE, SAND OR REMOVE OLD PAINT, YOU MAY RELEASE LEAD DUST. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

#### PRECAUTIONARY STATEMENTS

##### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**WARNING.** Causes skin irritation, Causes serious eye irritation. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not breathe vapors, spray mist, dust or chips from sanding. Avoid contact with skin, eyes or clothing. While spraying paint, or sanding surface, wear a mask or pesticide respirator approved by the National Institute for Occupational Safety and Health. Wear protective clothing (long sleeved cotton shirt, long pants, hat, gloves (such as nitril or butyl). Shoes and socks. Wash thoroughly with soap and water after handling and before eating, drinking, using tobacco or using the toilet. Remove contaminated clothing and wash before reuse. Use in well-ventilated area.

Follow manufacturers instructions for cleaning/maintaining Personal Protection Equipment (PPE). If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

##### FIRST AID

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advices.

**IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Never give anything by mouth to an unconscious person.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately; wash with soap and water. Rinse with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec - 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

##### PHYSICAL AND CHEMICAL HAZARDS (STORAGE)

Store locked up and well-ventilated area.

**KEEP FROM FREEZING. DO NOT THIN.**

**Spill:** Absorb with inert and dispose of as specified under "Clean Up".

**Clean Up:** Soap and Water.

**Disposal:** Empty containers may retain residue. Follow label warnings even after the container is emptied. To dispose of contaminated absorbent, container and unused contents contact your sanitation department or State-designated environmental agency.

Refer to Safety Data Sheet for additional health and safety information.

##### KEEP OUT OF REACH OF CHILDREN

**INGREDIENTS:** Polyurethane dispersion (Proprietary), Ethanol, 2-butoxy-,phosphate (78-51-3), Hydrocarbon wax (Proprietary), Silicone Dioxide (amorphous) (7631-86-9), 1-Methoxy-2-propanol (107-98-2), 2-Butoxyethanol (111-76-2).

**FACTORS BEYOND OUR CONTROL PREVENT US FROM ASSUMING RESPONSIBILITY FOR DAMAGE TO PROPERTY OR PERSON, EVEN WHEN THIS PRODUCT IS APPLIED ACCORDING TO DIRECTIONS. IN NO EVENT SHALL OUR LIABILITY EXCEED THE PURCHASE PRICE HEREOF.**

**THIS PRODUCT HAS A MAXIMUM VOC OF 275 G/L.**

**FOR WOOD SUBSTRATES ONLY.**

Item Number	Description	Size	Number per Case	Weight per Case
90101	Absco Solo Pro Clear - Satin	GL	4	38 lbs.
90105	Absco Solo Pro Clear - Satin	5G	N/A	48 lbs.
90301	Absco Solo Pro Clear - Matte	GL	4	38 lbs.
90305	Absco Solo Pro Clear - Matte	5G	N/A	48 lbs.



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit [canlakcoatings.com](http://canlakcoatings.com) or call us at **800-432-4333**.