



# PROFESSIONAL POLYURETHANE 350 VOC WOOD FLOOR FINISH



## SPECIFICATIONS:

VOC.....	350 g/L
Solids.....	56% - 58%
Flash Point.....	> 101°F (> 38°C)
Solvent .....	Mineral Spirits
Viscosity.....	130 - 230 cps
Odor .....	Solvent Like
Coverage.....	500 - 600 sq. ft/gal
Dry Time:.....	6 - 7 Hours
Color (Wet).....	Dark Amber
Color (Dry).....	Amber Clear
Sheens.....	Super High Gloss, Semi-Gloss, Satin, Matte
Sizes .....	1g & 5g Containers

## FEATURES

- Great Coverage & Low Odor
- Beautifies and Protects
- 350 VOC Formulation
- High Solids
- Commercial and Residential Use

## PROVEN QUALITY AND VALUE WITH CONSISTENT RESULTS

Absco Professional Polyurethane Wood Floor Finish makes it easy, with great coverage, easy application and multiple VOC formulations. Its oil-modified high solids formulation is durable, self-leveling and is formulated for beauty and protection. And this 350 VOC formula is designed for residential and commercial use.

**Please refer to the product label for specific surface preparation and application instructions.**



**ABSOLUTECOATINGS.COM**

OFFICE (800) 432-4333 | FAX (732) 821-8180

1999 Elizabeth Street • North Brunswick, NJ 08902