

CLEAR ECONOMY SEALER P.U.  
SERIES G920  
CLEAR**DESCRIPTION:**

G920 is two-component polyurethane sanding sealer from the series Verinlegno. It can be used for the finishing of flat panels, kitchen doors, moulding and all other components fabricated from wood and MDF. This product was designed to give good clarity and very easy sanding. It has excellent horizontal properties.

**PRODUCT DATA:**

PRODUCT CODE:	G920
VISCOSITY (20°C):	35 ± 2 sec (DIN 4)
SOLID % by WT:	44 ± 2 %
SOLID % by WT:	32 ± 2 % (at application)
VOC:	494 g/L
DENSITY:	8.067 lbs/gal
SHELF LIFE:	12 months

**MIXING RATIO:**

## PRODUCT FORMULATION

G920 POLYURETHANE:	2 parts
B40 CATALYST:	1 part
REDUCER:	400-050 (10-20 %)
POT LIFE:	4 hours at 68°F

**DRYING TIMES:**

THICKNESS APPLIED:	4-5 wet mils per coat
DUST FREE:	10 minutes
READY TO HANDLE:	40-50 minutes
READY TO SAND:	2-3 hours

**Note:** Drying times may vary depending on thickness applied, temperature and/or humidity.

**Warning:** Its is not recommended to use a product whose pot life has expired.

**Recoat:** Can be recoated without sanding within 2 hours, after 2 hours it must be sanded (#280-#400).

**APPLICATION:**

Surfaces should be well sanded and free of any traces of dust or oil or grease. Before application ensure that both products are thoroughly mixed together.

**APPLICATION EQUIPMENT:**

SPRAY GUN	
PRESSURE TANK	
AIR MIX	
FINISH THICKNESS:	4-5 wet mils
NUMBER OF COATS:	1-3 coats

**TYPICAL SYSTEM:**

TP WIPING STAIN		
G920 SEALER:	1-2 coats	4-5 wet mils
H410 TOPCOAT:	1 coat	4-5 wet mils

**STORAGE:**

Store in a dry and cool area. Close the container properly after use.



The customer is responsible for following the recommended application procedures. Failure to adhere to these specifications may result in poor appearance or failure of film. This product is for professional use only. Consult your local representative before applying with other manufacturer products. The customer should test the complete system for adhesion, compatibility and performance prior to full scale application. Please refer to the Safety Data Sheet (SDS) for safety information and precautions prior to using this product. We ONLY guarantee our product to conform to our quality. Our responsibility as manufacturer is limited to the cost of the product. Please feel free to contact us at (819) 367-2201 for any further inquiries regarding this product. All information on this product data sheet is subject to change without notice.