

Version : 1.0

SECTION 1) Chemical Product and Supplier's Identification

Product ID : IX-7868
Product Name : HAPs Free SNW Base
Revision Date : 02/18/2015
Supersedes Date :
Manufacturer's Name : Ceramic Industrial Coatings
Address : 325 Highway 81 Osseo, MN, US, 55369
Emergency Phone : Chemtrec: 1.800.424.9300 Date Printed : 02/18/2015
Information Phone : 763-424-2044

Product/Recommended Uses: Stain

SECTION 2) Hazards Identification

Classification:

Specific Target Organ Toxicity -Single Exposure (Respiratory Tract Irritation) - Category 3
Aspiration Hazard - Category 1
Skin Irritation - Category 2
Eye Irritation - Category 2A
Flammable Liquid Category 2
Germ Cell Mutagenicity - Category 1B
Carcinogenicity - Category 1B

Pictograms:



Signal Word:

Danger

Hazardous Statements - Physical:

Highly flammable liquid and vapor

Hazardous Statements - Health:

- May cause respiratory irritation
- May be fatal if swallowed and enters airways
- Causes skin irritation
- Causes serious eye irritation
- May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
- May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Hazardous Statements - Environmental:

- Not classified

Precautionary Statements - Prevention:

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Ground/bond container and receiving equipment.
- Use only outdoors or in a well-ventilated area.
- Use explosion-proof <electrical/ventilating/lighting/...> equipment.
- Keep container tightly closed.
- Use only non-sparking tools.
- Wash ? thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Take action to prevent static discharges.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.

Precautionary Statements - Response:

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water <or shower>.
- In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- Call a POISON CENTER/doctor/... if you feel unwell.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/?
- Do NOT induce vomiting.
- IF ON SKIN: Wash with plenty of water/?
- Specific treatment (see ? on this label).
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing. And wash it before reuse.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage:

Store in a well-ventilated place. Store locked up.

Store locked up.

Precautionary Statements - Disposal:

Dispose of contents/container to disposal recycling center.

Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

SECTION 3) Composition / Information on Ingredients

CAS	Chemical Name	% by Weight
0000067-64-1	ACETONE	29% - 49%
0000067-63-0	ISOPROPYL ALCOHOL	11% - 23%
0000064-17-5	ETHYL ALCOHOL	11% - 23%
0008030-30-6	NAPHTHA	10% - 21%
0000763-69-9	ETHYL-B-ETHOXY PROPIONATE	0.5% - 5.2%
0000107-87-9	METHYL PROPYL KETONE	0.3% - 3.7%
0009004-70-0	NITROCELLULOSE	0.2% - 2.6%

SECTION 4) First-Aid Measures

Inhalation:

Take precautions to ensure your own safety. (e.g. wear appropriate protective equipment. Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact:

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention. Store contaminated clothing under water and wash before re-use.

Eye Contact:

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion:

Rinse mouth. If you feel unwell/concerned: Get medical advice/attention.

SECTION 5) Fire-Fighting Measures

Suitable Extinguishing Media:

Use dry chemical, foam or carbon dioxide to extinguish fire.

Unsuitable Extinguishing Media:

Not available.

Fire-fighting Procedures:

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done so safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

Special Protective Actions:

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Care should always be exercised in dust/mist areas.

Use water to keep fire-exposed containers and the surroundings cool.

SECTION 6) Accidental Release Measures

Recommended Equipment:

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions:

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Emergency Procedure:

Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Collect with absorbent, non-combustible material into suitable containers.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Environmental Precautions:

Do not flush to sewer or waterways. Prevent release to the environment if possible.

SECTION 7) Handling and Storage

General:

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Storage Room Requirements:

Keep in a cool, dry, well-ventilated area, away from any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 8) Exposure Controls/ Personal Protection

Eye Protection:

Dust-proof goggles or safety glasses with side shields or vented/splash proof goggles. Contact lenses may absorb irritants. Particles may adhere to lenses and cause corneal damage.

Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. To prevent skin contact wear protective clothing covering all exposed areas. Avoid unnecessary skin contact.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA- Tables- Z1,2,3	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
ACETONE												

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
ACETONE		1188					

SECTION 9) Physical and Chemical Properties**Physical and Chemical Properties**

% Solids By Weight	1.53220%
% VOC	58.45937%
Density [lb/gal]	6.72958 lb/gal

Appearance	Liquid
Odor Description	Solvent
Odor Threshold	N.A.
pH	N.A.
Melting Point	N.A.
Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Flash Point Symbol	N.A.
Flash Point	4 °F
Evaporation Rate	N.A.
Flammability	N/A
Upper Explosion Level	N.A.
Lower Explosion Level	N.A.
Vapor Density	N.A.
Vapor Pressure	N.A.
Water Solubility	N.A.
Coefficient Water/Oil	N.A.
Auto Ignition Temp	N.A.
Decomposition Pt	N.A.
Viscosity	N.A.

SECTION 10) Stability and Reactivity

Stability:

Stable under normal conditions and use.

Conditions to Avoid:

Avoid great heat, sparks, flame, build up of static electricity and contact with incompatible materials.

Avoid temperature above maximum storage temperature.

Hazardous Polymerization:

Will not occur.

Incompatible Materials:

Not available.

Hazardous Decomposition Products:

No data available.

SECTION 11) Toxicological Information

Germ Cell Mutagenicity:

No data available.

Skin Corrosion/Irritation:

Causes mild skin irritation.

Carcinogenicity:

May cause cancer.

Specific Target Organ Toxicity - Single Exposure:

No data available.

Specific Target Organ Toxicity - Repeated Exposure:

No data available.

Serious Eye Damage/Irritation:

Causes serious eye irritation.

Aspiration Hazard:

No data available.

Respiratory/Skin Sensitization:

May cause an allergic skin reaction

Reproductive Toxicity:

No data available.

Acute Toxicity:

No data available.

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m³ (4-hour exposure) (29)
LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m³ (4-hour exposure) (29)
LD50 (oral, female rat): 5800 mg/kg (24)
LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)
LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)
LD50 (oral, mouse): 3000 mg/kg (32, unconfirmed)
LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

0008030-30-6 Aliphatic Naphtha

LD50 (oral, rat): >5 gm/kg

0000064-17-5 Ethanol

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m³ (4-hour exposure) (1, unconfirmed)
LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)
LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)
LD50 (oral, guinea pig): 5560 mg/kg (37)

0000067-63-0 ISOPROPANOL

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)
LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)
LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)
LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

0000067-63-0 ISOPROPYL ALCOHOL

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)
LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)
LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)
LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

0000107-87-9 Methyl n-propyl ketone

LD50 (oral, rat): 3017 mg/kg (cited as 3.73 mL/kg) (10)
LD50 (dermal, rabbit): 6472 mg/kg (cited as 8.00 mL/kg) (10)

Potential Health Effects - Miscellaneous

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0000067-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000107-87-9 METHYL PROPYL KETONE

May cause temporary upper respiratory and/or lung irritation with cough, difficult breathing, or shortness of breath. May cause any of the following central nervous system effects: drowsiness. May cause eye irritation with discomfort, tearing, or blurred vision.

0000763-69-9 ETHYL-B-ETHOXY PROPIONATE

Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

0009004-70-0 NITROCELLULOSE

The following medical conditions may be aggravated by overexposure: liver disease, kidney disorders.

SECTION 12) Ecological Information

Toxicity:

No data available.

Persistence and Degradability:

No data available.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects:

No data available.

Bio-accumulative Potential

0000067-64-1 ACETONE

Does not bioaccumulate

Persistence and Degradability

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

SECTION 13) Disposal Considerations

Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) Transport Information

U.S. DOT Information:

Shipping Name: Paint related material
UN/NA #: 1263 Hazard Class:3 Packing Group: II
Required Label(s): Flammable
Placards: Combustible

IMDG Information:

Shipping Name: Paint related material
UN/NA #: 1263 Hazard Class:3 Packing Group: III
Required Label(s): Combustible

IATA Information:

Shipping Name: Paint related material
UN/NA #: 1263 Hazard Class:3 Packing Group: II
Required Label(s): Combustible

SECTION 15) Regulatory Information


CAS	Chemical Name	% By Weight	Regulation List
-----	---------------	-------------	-----------------

SECTION 16) Other Information Including Information on Preparation and Revision of the SDS

Glossary:

ACGIH: American Conference of Governmental Industrial Hygienists
ANSI: American National Standards Institute
Canadian TDG: Canadian Transportation of Dangerous Goods
CAS: Chemical Abstract Service
Chemtrec: Chemical Transportation Emergency Center (US)
CHIP: Chemical Hazard Information and Packaging
DSL: Domestic Substances List
EC: Equivalent Concentration
EH40 (UK): HSE Guidance Note EH40 Occupational Exposure Limits
EPCRA: Emergency Planning and Community Right-To-Know Act
HMIS: Hazardous Material Information Service
LC: Lethal Concentration
LD: Lethal Dose
NFPA: National Fire Protection Association
OEL: Occupational Exposure Limits OSHA: Occupational Safety and Health Administration, US Department of Labor
PEL: Permissible Exposure Limit
SARA (Title III): Superfund Amendments and Reauthorization Act
SARA 313: Superfund Amendments and Reauthorization Act, Section 313
SCBA: Self-Contained Breathing Apparatus
STEL: Short Term Exposure Limit
TLV: Threshold Limit Value
TSCA: Toxic Substances Control Act Public Law 94-469
TWA: Time Weighted Value
US DOT: US Department of Transportation
WHMIS: Workplace Hazardous Materials Information System

HMIS



Chronic :



DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.
