According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

SECTION 1: Identification

Product identifier

Product name: Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss Product code: HC6200G, HC62005G

Recommended use of the product and restriction on use

Relevant identified uses: Finishes, Coatings, and Related Materials **Uses advised against:** Not determined or not applicable. **Reasons why uses advised against:** Not determined or not applicable.

Manufacturer or supplier details

Manufacturer: United States Absolute Coatings 1999 Elizabeth Street North Brunswick , New Jersey 089026316 (732)821-3200

Emergency telephone number:

United States CHEMTREC (703)527-3887 (24 HRS) (800)424-9300

SECTION 2: Hazard(s) identification

GHS classification:

Eye irritation, category 2A Skin sensitization, category 1 Reproductive toxicity, category 1B Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H317 May cause an allergic skin reaction

H360 May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

- H335 May cause respiratory irritation
- H319 Causes serious eye irritation

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

P272 Contaminated work clothing must not be allowed out of the workplace P280 Wear protective gloves/protective clothing/eye protection/face protection P201 Obtain special instructions before use P202 Do not handle until all safety precautions have been read and understood P271 Use only outdoors or in a well-ventilated area P264 Wash skin thoroughly after handling P302+P352 IF ON SKIN: Wash with plenty of water/ ... P333+P313 If skin irritation or rash occurs: Get medical advice/attention P321 Specific treatment (see ... on this label) P363 Wash contaminated clothing before reuse P308+P313 IF exposed or concerned: Get medical advice/attention P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P312 Call a POISON CENTER/doctor/.../if you feel unwell P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P337+P313 If eye irritation persists: Get medical advice/attention P405 Store locked up P403+P233 Store in a well-ventilated place. Keep container tightly closed P501 Dispose of contents/container to... Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 872-50-4	1-methyl-2-pyrrolidone	<7
CAS number: 121-44-8	Triethylamine	<3
CAS number: 126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	<0.2

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract. Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Immediate medical attention and special treatment

Specific treatment:

Effects are dependent on exposure (dose, concentration, contact time).

If respiratory symptoms persist, seek medical attention.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Country (Legal Basis)	Substance	Identifier	Permissible concentration
WEEL	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 10 ppm
	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 40 mg/m ³
United States(California)	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 1 ppm
	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 4 mg/m ³
ACGIH	Triethylamine	121-44-8	8-Hour TWA: 0.5 ppm

Occupational Exposure limit values:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

Country (Legal Basis)	Substance	Identifier	Permissible concentration	
	Triethylamine	121-44-8	15-Minute STEL: 1 ppm	
NIOSH	Triethylamine	121-44-8	IDLH: 200 ppm	
OSHA	Triethylamine	121-44-8	TWA: 10 ppm	
	Triethylamine	121-44-8	TWA: 40 mg/m ³	
	Triethylamine	121-44-8	STEL: 15 ppm	
	Triethylamine	121-44-8	STEL: 60 mg/m ³	

Biological limit values:

(Country (Legal Basis)		lden tifier	Determinant	Specimen		Permissible limits
4	ACGIH	1-methyl-2-pyrrolidone		5-Hydroxy-N-methyl-2- pyrrolidone	Urine	End of shift	100 mg/L

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Golden brown liquid
Odor	Mild

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

Odor threshold	N/A
рН	8 - 9
Melting point/freezing point	N/A
Initial boiling point/range	<100°C
Flash point (closed cup)	N/A
Evaporation rate	Faster than water
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	2.6% by volume
Vapor pressure	N/A
Vapor density	N/A
Density	1.02 +/- 0.02 g/cc
Relative density	1.02 +/- 0.02
Solubilities	Miscible with water
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

Other information

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met. Product data: No data available. Substance data:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Page 7 of 12

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

Name	Route	Result	
1-methyl-2-pyrrolidone	oral	LD50 Rat: 4150 mg/kg	
	inhalation	LC50 Rat: >5.1 mg/L (4 hours)	
	dermal	LD50 Rat: >5000 mg/kg	
Triethylamine	oral	LD50 Rat: 730 mg/kg	
	inhalation	LC50 Rat: 3496 ppmV	
	dermal	LD50 Rabbit: 580 mg/kg	
2,4,7,9-tetramethyldec-5-	oral	LD50 Rat: >5000 mg/kg	
yne-4,7-diol	dermal	LD50 Rat: >2000 mg/kg	

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Causes skin irritation.
Triethylamine	Causes severe skin burns and eye damage.

Serious eye damage/irritation

Assessment:

Causes serious eye irritation.

Product data:

No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Causes serious eye irritation.
2,4,7,9-tetramethyldec-5- yne-4,7-diol	Causes serious eye damage.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:

No data available.

Substance data:

Name	Result
2,4,7,9-tetramethyldec-5- yne-4,7-diol	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC): None of the ingredients are listed.

National Toxicology Program (NTP): None of the ingredients are listed.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

OSHA Carcinogens: Not applicable

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment:

May damage fertility or the unborn child.

Product data:

No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	May damage fertility or the unborn child (developmental effects).

Specific target organ toxicity (single exposure)

Assessment:

May cause respiratory irritation.

Product data:

No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	May cause respiratory irritation.
Triethylamine	May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met. **Product data:** No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Page 9 of 12

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

Substance data:

Name	Result
1-methyl-2-pyrrolidone	LC50 Oncorhynchus mykiss: 500 mg/L (96 hours)
Triethylamine	LC50 Onchorhynchus mykiss: 36 mg/L (96 hours)
	LC50 Cyprinus carpio: 42 mg/L (96 hours)
	LC50 Daphnia magna : 88 mg/L (48 hours)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met. **Product data:** No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	NOEC Daphnia magna: 12.5 mg/L (21 days)
Triethylamine	EC50 Danio rerio: 53 mg/L (7 days)

Persistence and degradability

Product data: No data available.

Substance data:	
Name	Result
1-methyl-2-pyrrolidone	Readily biodegradable.
Triethylamine	Readily biodegradable.
2,4,7,9-tetramethyldec-5- yne-4,7-diol	Does not readily biodegrade.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Low potential for bioaccumulation.
Triethylamine	BCF: 0.5 L/kg ww
2,4,7,9-tetramethyldec-5- yne-4,7-diol	BCF: 24

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Adsorption to the solid soil phase is not expected.
Triethylamine	Koc at 20°C: 107.2
2,4,7,9-tetramethyldec-5- yne-4,7-diol	Koc at 20°C: 43.05

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT..

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance data: PBT assessment:

I DI USSESSITET	••	
1-methyl-2-pyrrol	idone Sul	bstance is not PBT.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Page 10 of 12

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

Triethylamine	Substance is not PBT.
2,4,7,9-tetramethyldec-5- yne-4,7-diol	Substance is not PBT.
vPvB assessment:	•
1-methyl-2-pyrrolidone	Substance is not vPvB.
Triethylamine	Substance is not vPvB.
2,4,7,9-tetramethyldec-5- yne-4,7-diol	Substance is not vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.12.2020 Revision date: 05.12.2020

Page 11 of 12

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

Special precautions for user

None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

872-50-4	1-methyl-2-pyrrolidone	Listed
121-44-8	Triethylamine	Listed
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals:

872-50-4	1-methyl-2-pyrrolidone	Listed
121-44-8	Triethylamine	Listed
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	Not Listed

CERCLA:

121-44-8 Triethylamine Listed 5000 Lbs
--

RCRA:

121-44-8	Triethylamine	

U404

Listed

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

872-50-4	1-methyl-2-pyrrolidone	Listed
121-44-8	Triethylamine	Listed
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	Not Listed

New Jersey Right to Know:

872-50-4	1-methyl-2-pyrrolidone	Listed
121-44-8	Triethylamine	Listed
126-86-3		Not Listed

New York Right to Know:

872-50-4	1-methyl-2-pyrrolidone	Not Listed
121-44-8	Triethylamine	Listed
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	Not Listed

Pennsylvania Right to Know:

872-50-4	1-methyl-2-pyrrolidone	Listed
121-44-8	Triethylamine	Listed
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	Not Listed

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial preparation date: 05.12.2020

Revision date: 05.12.2020

Radiance Oil Modified Waterborne Hardwood Floor Finish Gloss

California Proposition 65:

WARNING: This product can expose you to 1-methyl-2-pyrrolidone; which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-1-0

HMIS: 2*-1-0-X Initial preparation date: 05.12.2020 Revision date: 05.12.2020 Revision Notes:

Revision Date	Notes
2020-05-04	Version 04

End of Safety Data Sheet