



CLASSIC WORLD MOISTURE CURE URETHANE

OVERVIEW: Tough Finish That's Great for High Traffic Areas

Sampson Moisture Cure Urethane is a urethane finish that offers toughness and flexibility, with resistance to grease, water and chemicals. Perfect for high traffic areas, the formula offers outstanding resistance to abrasion and wear and can be used on all types of wood floors.

PHYSICAL CHARACTERISTICS

- Sheens: Super High Gloss, Semi Gloss & Satin
- Color: Clear
- Solids: 40 - 46%
- Flash Point: 81° F (27.2° C)
- VOC Content: 350 VOC
- Odor: Solvent Like
- Gloss Level (60%): Minimum 85 GU for Gloss
..... 55 - 65 GU for Semi Gloss
..... 25 - 35 GU for Satin
- Stability: 6 Months
- Packaging Size: 5 Gallon, 1 Gallon & Quart

APPLICATION CHARACTERISTICS

- Dry Color Clarity: Clear
- Coverage Rate: 500 sq. ft. (Varies with surface porosity)
- Dry Time: To Touch: 1 - 2 Hours (May vary with air moisture)
..... To Screen: 6 - 8 Hours
- Fully Cured: 7 Days
- Recommended
- Film Thickness: Wet 2-3 mils
- Leveling: Very Good
- Defoaming: Excellent
- Working Temp: 65 - 90° F
- Storage Temp: 50 - 90° F
- Thin With: Do Not Thin
- Clean Up: Xylene or Lacquer Thinner
- Application Methods: T-Bar Applicator, Brush, or Roller
- Professional Market: Commercial

FEATURES

- Perfect for High Traffic Areas
- Offers Outstanding Resistance to Abrasion and Wear
- Tough and Flexible Finish, with Resistance to Grease, Water and Chemicals

BENEFITS

- Offers Outstanding Resistance to Abrasion and Wear
- Tough and Flexible Finish, with Resistance to Grease, Water and Chemicals
- Perfect Finish for High Traffic Areas
- Available in 350 VOC Formulation

sampsoncoatings.com
 info@sampsoncoatings.com
 800-368-2677
 1999 Elizabeth St.
 North Brunswick, NJ 08902

MADE IN THE U.S.A.

