



PHYSICAL CHARACTERISTICS

Sheens: High Gloss, Semi Gloss, Satin & Matte

Color: Slightly Amber

Solids: 28 - 30%

VOC Content: 200 VOC

Odor: Mild Solvent

Gloss Level (60%): Minimum 85 GU for Gloss
45 - 50 GU for Semi Gloss
25 - 35 GU for Satin
5 - 15 GU for Matte

Stability: 1 Year

Packaging Size: 5 Gallon & 1 Gallon

APPLICATION CHARA	CTERISTICS
Dry Color Clarity:	.Slightly Amber
Coverage Rate:	.650 sq. ft. (Varies with surface porosity)
Dry Time:	.1-3 Hours
Fully Cured:	.7 - 8 Days
Leveling:	.Very Good
Defoaming:	.Excellent
Working Temp:	.Room Temperature 65 – 75° F
Application Methods:	.T-Bar Applicator, Brush, or Roller
Storage Temp:	.Between 50 - 78° F
Professional Market:	.Commercial &

Residential Use

RADIANCE OIL MODIFIED WATERBORNE HARDWOOD FLOOR FINISH

OVERVIEW: Great Coverage With Easy Application

Sampson Radiance is a waterborne finish that gives a rich traditional oil look with no catalyst or cross linker needed. It is quick drying for faster recoating, features enhanced durability with excellent film build, and is recommended for commercial and residential applications.

FEATURES

- Rich, Traditional Oil Look
- Great Coverage with Easy Application
- · Quick Drying
- Recommend for Residential and Commerical applications

BENEFITS

- Low Odor and Low VOC
- No Catalyst or Cross Linker Needed
- Faster Recoat
- Enhanced Durability with Excellent Film Build

sampsoncoatings.com info@sampsoncoatings.com 800-368-2677 1999 Elizabeth St. North Brunswick, NJ 08902

