According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

SECTION 1: Identification

Product Identifier

Product Name: Polo 1K Semi, Satin, Matte

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Finishes, Coatings and Related Materials

Uses Advised Against: For Professional Use Only

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer: **United States**

Canlak Coatings 1999 Elizabeth Street North Brunswick, New Jersey 089026316 (732)821-3200 www.poloplaz.com

Emergency Telephone Number:

United States

Infotrac

1-800-535-5053 (24/7)

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin irritation, category 2 Serious eye damage, category 1 Skin sensitization, category 1

Label elements

Hazard Pictograms:





Signal Word: Danger Hazard statements:

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H318 Causes serious eye damage

Precautionary Statements:

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace

P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P321 Specific treatment (see ... on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention



Page 1 of 13



According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

P362 Take off contaminated clothing and wash it before reuse

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER/doctor/...

P501 Dispose of contents/container to...

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 34590-94-8	(2-Methoxymethylethoxy)propanol	3-6
CAS Number: 107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	1-4
CAS Number: 25498-49-1	[2-(2-methoxymethylethoxy)methylethoxy]propanol	1-3
CAS Number: 112945-52-5	Silica, amorphous, fumed, crystfree	0.5-2

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Page 2 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020 Page 3 of 13

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Silica, amorphous, fumed, crystfree	112945-52- 5	REL-TWA: 6 mg/m³ (Silica, amorphous [up to 19 hr])
	Silica, amorphous, fumed, crystfree	112945-52- 5	IDLH: 3000 mg/m³ (Silica, amorphous)
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	REL-TWA: 360 mg/m³ (100 ppm [up to 10 hr])
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	15-Minute STEL: 540 mg/m³ (150 ppm)
	(2-Methoxymethylethoxy)propanol	34590-94-8	IDLH: 600 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	STEL: 900 mg/m³ ([150 ppm])
	(2-Methoxymethylethoxy)propanol	34590-94-8	REL-TWA: 600 mg/m³ (100 ppm [up to 10 hr])
OSHA	Silica, amorphous, fumed, crystfree	112945-52- 5	8-Hour TWA: 0.8 mg/m³ (Silica: Amorphous, including natural diatomaceous earth)
	(2-Methoxymethylethoxy)propanol	34590-94-8	TWA: 600 mg/m³ ([100 ppm])
	(2-Methoxymethylethoxy)propanol	34590-94-8	STEL: 900 mg/m³ ([150 ppm])
ACGIH	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	8-Hour TWA: 50 ppm
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	15-Minute STEL: 100 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	TLV-TWA: 50 ppm (8 hr)
	Silica, amorphous, fumed, crystfree	112945-52- 5	8-Hour TWA: 3 mg/m³ (Particles, insoluble or poorly soluble, N.O.S, respirable)
	Silica, amorphous, fumed, crystfree	112945-52- 5	8-Hour TWA: 10 mg/m³ (Particles, insoluble or poorly soluble, N.O.S, inhalable)

Page 4 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020 Page 14.10

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States(California)	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	8-Hour TWA-PEL: 360 mg/m ³ (100 ppm)
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	15-Minute STEL: 540 mg/m³ (150 ppm)
	Silica, amorphous, fumed, crystfree	112945-52- 5	8-Hour TWA: 10 mg/m³ (Particulates not otherwise regulated, total dust)
	Silica, amorphous, fumed, crystfree	112945-52- 5	8-Hour TWA: 5 mg/m³ (Particulates not otherwise regulated, respirable fraction)
	(2-Methoxymethylethoxy)propanol	34590-94-8	15-Minute STEL: 900 mg/m³ ([150 ppm])
	(2-Methoxymethylethoxy)propanol	34590-94-8	8-Hour TWA-PEL: 600 mg/m ³ ([100 ppm])

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Page 5 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Whitish liquid
Odor	Sweet
Odor threshold	N/A
pH	7 - 9
Melting point/freezing point	N/A
Initial boiling point/range	> 93C
Flash point (closed cup)	> 93C
Evaporation rate	N/A
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	N/A
Vapor pressure	N/A
Vapor density	N/A
Density	8.6 +/- 0.20 Lbs./Gal.
Relative density	1.03 +/- 0.03
Solubilities	Dispersible in water
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

Other Information

VOC g/l less water	< 275 g/l less water	

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Page 6 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
1-methoxy-2-propanol	oral	LD50 Rat: 3739 mg/kg
monopropylene glycol methyl ether	dermal	LD50 Rat: > 2000 mg/kg
l ether	inhalation	LC50 Rat: >7000 ppmV (6 hr [vapor])
[2-(2-	oral	LD50 Rat: 3400 mg/kg
methoxymethylethoxy)methyle thoxy]propanol	dermal	LD50 Rabbit: 15,440 mg/kg
(2- Methoxymethylethoxy)propano		LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rabbit: 9510 mg/kg
Silica, amorphous, fumed, crystfree	oral	LD50 rat: 3160 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Silica, amorphous, fumed,	Causes skin irritation.
crystfree	

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Silica, amorphous, fumed,	Causes serious eye irritation.
crystfree	

Respiratory or Skin Sensitization

Assessment:

Page 7 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020 Page

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

May cause an allergic skin reaction.

Product Data:No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Silica, amorphous, fumed, crystfree	Group 3
1-methoxy-2-propanol monopropylene glycol methyl ether	Not Applicable
(2- Methoxymethylethoxy)propano I	Not Applicable
[2-(2- methoxymethylethoxy)methyle thoxy]propanol	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Silica, amorphous, fumed, crystfree	Not Applicable
1-methoxy-2-propanol monopropylene glycol methyl ether	Not Applicable
(2- Methoxymethylethoxy)propano	Not Applicable
[2-(2- methoxymethylethoxy)methyle thoxy]propanol	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Page 8 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available. **Substance Data:**

Name	Result
Silica, amorphous, fumed, crystfree	May cause respiratory irritation.
1-methoxy-2-propanol monopropylene glycol methyl ether	May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available. **Information on Likely Routes of Exposure:**

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available. **Other Information:**No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
[2-(2-	Fish LC50 Pimephales promelas: 11,619 mg/L (96 hr)
methoxymethylethoxy)methyle thoxy]propanol	Aquatic Plants EC50 Raphidocelis subcapitata: 21,010 mg/L (96 hr [growth rate])
	Aquatic Invertebrates LC50 Daphnia magna: >10,000 mg/L (48 hr [mortality])
1-methoxy-2-propanol	Fish LC50 Oncorhynchus mykiss: >= 1000 mg/L (96 hr)
monopropylene glycol methyl ether	Aquatic Invertebrates EC50 Daphnia magna: > 500 mg/L (48 hr [mobility])
ether	Aquatic Plants EC50 Skeletonema costatum: 6745 mg/L (72 hr [growth rate])
(2-	Aquatic Plants EC50 Freshwater green algea: > 969 mg/L (72 hr [biomass])
Methoxymethylethoxy)propano	Fish LC50 Poecilia reticulata: >1000 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 1919 mg/L (48 hr [mortality])

Chronic (Long-Term) Toxicity

Page 9 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
(2- Methoxymethylethoxy)propano	Aquatic Invertebrates NOEC Daphnia magna: >=0.5 mg/L (22 d [reproduction])

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
[2-(2- methoxymethylethoxy)methyle thoxy]propanol	The substance is Readily biodegradable 53% after 28 days [O2 consumption]
	The substance is readily biodegradable. 79 % degradation in water, measured by O2 consumption, after 28 days.
1-methoxy-2-propanol monopropylene glycol methyl ether	The substance is readily biodegradable. 96% degradation in water, measured by DOC removal after 28 days.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

abstance batar		
Name	Result	
[2-(2- methoxymethylethoxy)methyle thoxy]propanol	The substance has low potential of bioaccumulation. {BCF: 1.162, estimated using the EPIWin QSAR approach}	
(2- Methoxymethylethoxy)propano I	The substance is not expected to bioaccumulate (Log Kow: <1).	
1-methoxy-2-propanol monopropylene glycol methyl ether	The substance is not expected to bioaccumulate (log Pow: < 1 at 20 °C).	

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
(2- Methoxymethylethoxy)propano	The substance is highly mobile, therefore, adsorption to soil and sediment is not expected (Log Koc $<$ 1).
1-methoxy-2-propanol monopropylene glycol methyl ether	The endpoint is not applicable because the substance has a low octanol water partition coefficient.

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

Page 10 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

PBT assessment:

[2-(2- methoxymethylethoxy)methyl ethoxy]propanol	Substance is not PBT.
1-methoxy-2-propanol monopropylene glycol methyl ether	The substance is not PBT.
(2- Methoxymethylethoxy)propan ol	The substance is not PBT.

vPvB assessment:

r vb d55e55illelit.		
[2-(2- methoxymethylethoxy)methyl ethoxy]propanol	Substance is not vPvB.	
1-methoxy-2-propanol monopropylene glycol methyl ether	The substance is not vPvB.	
(2- Methoxymethylethoxy)propan ol	The substance is not vPvB.	

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	Not Regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	Not Regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None

Page 11 of 13

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Page 12 of 13

Listed

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Charial Duagantians for Hear	Nana
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not Regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

34590-94-8

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

(2-Methoxymethylethoxy)propanol

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

CE	CERCLA:					
	107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether		100 lbs for RCRA D001		
D.C.	DODA:					

RCRA:

107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed	D001

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

New Jersey Right to Know:

107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

New York Right to Know:

107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

Pennsylvania Right to Know:

107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

California Proposition 65:

▲WARNING: This product can expose you to Formaldehyde; which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Additional information: Not determined.

SECTION 16: Other Information

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.13.2020 Page 13 of 13

Revision date: 03.03.2025

Polo 1K Semi, Satin, Matte

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-1-0 **HMIS:** 2-1-0

Initial Preparation Date: 02.13.2020

Revision date: 03.03.2025

End of Safety Data Sheet