

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 1 of 14

Cleanwoode

SECTION 1: Identification

Product Identifier

Product Name: Cleanwoode

Product code: WCW37071 - WCW37074



Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Not determined or not applicable.

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Absolute Coatings

1999 Elizabeth Street

North Brunswick, New Jersey 089026316

(732)821-3200

Emergency Telephone Number:

United States

CHEMTREC

(703)527-3887 (24 HRS)

(800)424-9300

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin irritation, category 2

Eye irritation, category 2A

Aspiration hazard, category 1

Flammable liquids, category 2

Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 1

Specific target organ toxicity - single exposure, category 3, narcotic effects

Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H225 Highly flammable liquid and vapor

H315 Causes skin irritation

H319 Causes serious eye irritation

H304 May be fatal if swallowed and enters airways

H361 Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 2 of 14

Cleanwoode

H370 Causes damage to organs (or state all organs affected, if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H336 May cause drowsiness or dizziness

H373 May cause damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Precautionary Statements:

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P271 Use only outdoors or in a well-ventilated area

P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P321 Specific treatment (see ... on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention

P331 Do NOT induce vomiting

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/ ...

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use ... to extinguish

P308+P313 IF exposed or concerned: Get medical advice/attention

P307+P311 IF exposed: Call a POISON CENTER or doctor/physician

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312 Call a POISON CENTER/doctor/.../if you feel unwell

P314 Get medical advice/attention if you feel unwell

P405 Store locked up

P403+P235 Store in a well-ventilated place. Keep cool

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P501 Dispose of contents/container to...

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

| Identification | Name | Weight % |
|-------------------------|---------|----------|
| CAS Number: 108-88-3 | Toluene | <68.83 |

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 3 of 14

Cleanwoode

| | | |
|------------------------|-------------|-------|
| CAS Number: 67-56-1 | Methanol | <2.34 |
| CAS Number: 67-64-1 | Acetone | <9.36 |
| CAS Number: 67-63-0 | Propan-2-ol | <18.6 |

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

This product presents an aspiration hazard. If aspiration is suspected, seek emergency medical treatment. If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and pneumonitis. Symptoms may include shortness of breath, dry cough and irritation of the nose, eyes, lips, mouth and throat.

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 4 of 14

Cleanwoode

Causes damage to organs. Effects are dependent on exposure (dose, concentration, contact time). Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Symptoms of pulmonary edema may be delayed.

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

May cause damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

Skin/eye burns require immediate treatment.

If exhibiting symptoms of exposure, seek prompt medical attention.

Overexposure via inhalation requires urgent medical treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air.

They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes.

Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions.

Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 5 of 14

Cleanwoode

safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 6 of 14

Cleanwoode

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

| Country (Legal Basis) | Substance | Identifier | Permissible concentration |
|---------------------------|-------------|------------|--|
| ACGIH | Toluene | 108-88-3 | TWA: 20 ppm |
| | Methanol | 67-56-1 | 8-Hour TWA: 200 ppm |
| | Methanol | 67-56-1 | 15-Minute STEL: 250 ppm |
| | Acetone | 67-64-1 | 8-Hour TWA: 250 ppm |
| | Acetone | 67-64-1 | 15-Minute STEL: 500 ppm |
| | Propan-2-ol | 67-63-0 | 15-Minute STEL: 400 ppm |
| | Propan-2-ol | 67-63-0 | 8-Hour TWA: 200 ppm |
| NIOSH | Toluene | 108-88-3 | TWA: 375 mg/m ³ (100 ppm) |
| | Toluene | 108-88-3 | STEL: 560 mg/m ³ (150 ppm) |
| | Methanol | 67-56-1 | REL-TWA: 260 mg/m ³ (200 ppm [for up to a 10-hour workday during a 40-hour workweek]) |
| | Methanol | 67-56-1 | 15-Minute STEL: 325 mg/m ³ (250 ppm) |
| | Methanol | 67-56-1 | IDLH: 6000 ppm |
| | Acetone | 67-64-1 | REL-TWA: 590 mg/m ³ (250 ppm [up to 10-hr]) |
| | Acetone | 67-64-1 | IDLH: 2500 ppm |
| | Propan-2-ol | 67-63-0 | IDLH: 2000 ppm |
| | Propan-2-ol | 67-63-0 | 15-Minute STEL: 500 ppm (1,225 mg/m ³) |
| United States | Propan-2-ol | 67-63-0 | REL-TWA: 400 ppm (980 mg/m ³ - up to 10 hrs.) |
| | Toluene | 108-88-3 | PEL: 300 ppm (Ceiling) |
| | Toluene | 108-88-3 | PEL: 200 ppm (TWA) |
| United States(California) | Toluene | 108-88-3 | PEL: 500 ppm (Peak 10 mins) |
| | Toluene | 108-88-3 | PEL: 37 mg/m ³ (10 ppm) |
| | Toluene | 108-88-3 | STEL: 560 mg/m ³ (150 ppm) |
| | Toluene | 108-88-3 | Ceiling Limit: 500 ppm |
| | Methanol | 67-56-1 | 15-Minute STEL: 325 mg/m ³ (250 ppm) |
| | Methanol | 67-56-1 | PEL Ceiling: 1000 ppm |
| | Methanol | 67-56-1 | 8-Hour TWA: 260 mg/m ³ (200 ppm) |
| | Acetone | 67-64-1 | STEL: 1780 mg/m ³ (750 ppm) |
| | Acetone | 67-64-1 | 8-Hour TWA-PEL: 1200 mg/m ³ (500 ppm) |
| | Acetone | 67-64-1 | Ceiling Limit: 3000 ppm |

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 7 of 14

Cleanwoode

| Country (Legal Basis) | Substance | Identifier | Permissible concentration |
|-----------------------|-------------|------------|---|
| OSHA | Propan-2-ol | 67-63-0 | 8-Hour TWA-PEL: 980 mg/m ³ (400 ppm - Cal/OSHA) |
| | Propan-2-ol | 67-63-0 | 15-Minute STEL: 1225 mg/m ³ (500 ppm - Cal/OSHA) |
| | Methanol | 67-56-1 | 8-Hour TWA-PEL: 260 mg/m ³ (200 ppm) |
| | Methanol | 67-56-1 | 15-Minute STEL: 325 mg/m ³ (250 ppm) |
| | Acetone | 67-64-1 | 8-Hour TWA-PEL: 2400 mg/m ³ (1000 ppm) |
| | Acetone | 67-64-1 | STEL: 2400 mg/m ³ (1000 ppm) |
| | Acetone | 67-64-1 | TWA: 1800 mg/m ³ (750 ppm) |
| | Propan-2-ol | 67-63-0 | 8-Hour TWA-PEL: 400 ppm (OSHA PEL TWA 980 mg/m ³) |

Biological Limit Values:

| Country (Legal Basis) | Substance | Identifier | Determinant | Specimen | Sampling time | Permissible limits |
|-----------------------|-----------|------------|-------------|----------|---------------|--------------------|
| ACGIH | Methanol | 67-56-1 | Methanol | Urine | End of Shift | 15 mg/L |
| | Acetone | 67-64-1 | Acetone | Urine | End of shift | 25 mg/L |

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General Hygienic Measures:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 8 of 14

Cleanwoode

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

| | |
|---|----------------------------------|
| Appearance | Liquid |
| Odor | solvent like |
| Odor threshold | Not determined |
| pH | Not determined or not available. |
| Melting point/freezing point | Not determined or not available. |
| Initial boiling point/range | Not determined |
| Flash point (closed cup) | < 22 ° F |
| Evaporation rate | Not determined |
| Flammability (solid, gas) | No data available |
| Upper flammability/explosive limit | Not determined or not available. |
| Lower flammability/explosive limit | Not determined or not available. |
| Vapor pressure | Not determined or not available. |
| Vapor density | Not determined or not available. |
| Density | 7.03 lb/gal |
| Relative density | 0.84 |
| Solubilities | miscible in water |
| Partition coefficient (n-octanol/water) | Not determined |
| Auto/Self-ignition temperature | Not determined |
| Decomposition temperature | Not determined |
| Dynamic viscosity | Not determined |
| Kinematic viscosity | Not determined |
| Explosive properties | Not determined |
| Oxidizing properties | Not determined |

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 9 of 14

Cleanwoode

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

| Name | Route | Result |
|-------------|------------|--|
| Toluene | oral | LD50 Rat: 5000 mg/kg |
| | dermal | LD50 Rabbit: 12,000 mg/kg |
| | inhalation | LC50 Rat: 25.7 mg/L (4 h [Vapor]) |
| Methanol | oral | LD50 N/A: 100 mg/kg (ATE (based on hazard classification)) |
| | dermal | LD50 N/A: 300 mg/kg (ATE (based on hazard classification)) |
| | inhalation | LC50 N/A: 3 mg/L (ATE (based on hazard classification)) |
| Acetone | oral | LD50 Rat: 5800 mg/kg |
| | inhalation | LC50 Rat: 76 mg/L (4 hr (vapor)) |
| | dermal | LD50 Rabbit: > 7426 mg/kg |
| Propan-2-ol | oral | LD50 Rabbit: 6410 mg/kg |
| | dermal | LD50 Rabbit: 12,800 mg/kg |
| | inhalation | LC50 Rat: 72.6 mg/L (4 hr) |

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

| Name | Result |
|---------|-------------------------|
| Toluene | Causes skin irritation. |

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

| Name | Result |
|-------------|--------------------------------|
| Acetone | Causes serious eye irritation. |
| Propan-2-ol | Causes serious eye irritation. |

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 10 of 14

Cleanwoode

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

| Name | Classification |
|-------------|----------------|
| Toluene | Group 3 |
| Methanol | Not Applicable |
| Acetone | Not Applicable |
| Propan-2-ol | Group 3 |

National Toxicology Program (NTP):

| Name | Classification |
|-------------|----------------|
| Methanol | Not Applicable |
| Acetone | Not Applicable |
| Propan-2-ol | Not Applicable |

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment:

Suspected of damaging fertility or the unborn child.

Product Data:

No data available.

Substance Data:

| Name | Result |
|---------|---|
| Toluene | Suspected of damaging the unborn child. |

Specific Target Organ Toxicity (Single Exposure)

Assessment:

Causes damage to organs.

May cause drowsiness or dizziness.

Product Data:

No data available.

Substance Data:

| Name | Result |
|-------------|--|
| Toluene | May cause drowsiness or dizziness. |
| Methanol | Causes damage to Optic nerve (nervus opticus), central nervous system. |
| Acetone | May cause drowsiness or dizziness. |
| Propan-2-ol | May cause drowsiness or dizziness. |

Specific Target Organ Toxicity (Repeated Exposure)

Assessment:

May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 11 of 14

Cleanwoode

Product Data:

No data available.

Substance Data:

| Name | Result |
|---------|--|
| Toluene | May cause damage to organs (central nervous system; kidneys; liver) through prolonged or repeated exposure. Exposure to the substance may increase noise-induced hearing loss. |

Aspiration toxicity

Assessment:

May be fatal if swallowed and enters airways.

Product Data:

No data available.

Substance Data:

| Name | Result |
|---------|---|
| Toluene | May be fatal if swallowed and enters airways. |

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

| Name | Result |
|---------|---|
| Acetone | Fish LC50 <i>Oncorhynchus mykiss</i> : 5540 mg/L (4 days) |

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Persistence and Degradability

Product Data: No data available.

Substance Data:

| Name | Result |
|-------------|--|
| Toluene | Readily biodegradable in water. |
| Methanol | Readily biodegradable (97% degradation after 20 days). |
| Acetone | Readily biodegradable (90.9% degradation after 28 days). |
| Propan-2-ol | Readily biodegradable in water. |

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

| Name | Result |
|---------|---------|
| Toluene | BCF: 90 |

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 12 of 14

Cleanwoode

| Name | Result |
|-------------|---|
| Methanol | Methanol does not significantly bioaccumulate in fish. Experimental BCFs of < 10 in fish species. |
| Acetone | Very low potential for bioaccumulation (BCF: 3). |
| Propan-2-ol | Not expected to bioaccumulate (log Kow: 0.05). |

Mobility in Soil

Product Data: No data available.

Substance Data:

| Name | Result |
|----------|---|
| Toluene | Moderately Mobile (Calculated Koc: 205) |
| Methanol | Highly mobile (Koc: 0.13 - 0.61 dimensionless). |

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

| | |
|-------------|----------------------------|
| Methanol | This substance is not PBT. |
| Acetone | This substance is not PBT. |
| Propan-2-ol | This substance is not PBT. |

vPvB assessment:

| | |
|-------------|-----------------------------|
| Methanol | This substance is not vPvB. |
| Acetone | This substance is not vPvB. |
| Propan-2-ol | This substance is not vPvB. |

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

| | |
|-------------------------------|-------|
| UN Number | 1263 |
| UN Proper Shipping Name | PAINT |
| UN Transport Hazard Class(es) | 3 |
| Packing Group | III |
| Environmental Hazards | None |
| Special Precautions for User | None |



Safety Data Sheet


According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025


Page 13 of 14

Cleanwoode

International Maritime Dangerous Goods (IMDG)

| | |
|-------------------------------|---|
| UN Number | 1263 |
| UN Proper Shipping Name | paint |
| UN Transport Hazard Class(es) | 3  |
| Packing Group | III |
| Environmental Hazards | None |
| Special Precautions for User | None |

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

| | |
|-------------------------------|---|
| UN Number | 1263 |
| UN Proper Shipping Name | Paint |
| UN Transport Hazard Class(es) | 3  |
| Packing Group | III |
| Environmental Hazards | None |
| Special Precautions for User | None |

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

| | | |
|----------|-------------|--------|
| 108-88-3 | Toluene | Listed |
| 67-56-1 | Methanol | Listed |
| 67-63-0 | Propan-2-ol | Listed |

CERCLA:

| | | | |
|----------|----------|--------|----------|
| 108-88-3 | Toluene | Listed | 1000 |
| 67-56-1 | Methanol | Listed | 5000 lbs |
| 67-64-1 | Acetone | Listed | 5000 lb |

RCRA:

| | | | |
|----------|----------|--------|------|
| 108-88-3 | Toluene | Listed | U220 |
| 67-56-1 | Methanol | Listed | U154 |
| 67-64-1 | Acetone | Listed | U002 |

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

| | | |
|----------|-------------|--------|
| 108-88-3 | Toluene | Listed |
| 67-56-1 | Methanol | Listed |
| 67-64-1 | Acetone | Listed |
| 67-63-0 | Propan-2-ol | Listed |

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.06.2025

Page 14 of 14

Cleanwoode

New Jersey Right to Know:

| | | |
|----------|-------------|--------|
| 108-88-3 | Toluene | Listed |
| 67-56-1 | Methanol | Listed |
| 67-64-1 | Acetone | Listed |
| 67-63-0 | Propan-2-ol | Listed |


New York Right to Know:

| | | |
|----------|-------------|--------|
| 108-88-3 | Toluene | Listed |
| 67-56-1 | Methanol | Listed |
| 67-64-1 | Acetone | Listed |
| 67-63-0 | Propan-2-ol | Listed |

Pennsylvania Right to Know:

| | | |
|----------|-------------|--------|
| 108-88-3 | Toluene | Listed |
| 67-56-1 | Methanol | Listed |
| 67-64-1 | Acetone | Listed |
| 67-63-0 | Propan-2-ol | Listed |

California Proposition 65:

 **WARNING:** This product can expose you to chemicals including Toluene and Methanol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-3-0

HMIS: 2*-3-0

Initial Preparation Date: 06.06.2025

End of Safety Data Sheet