



# PROFESSIONAL POLYURETHANE 350 VOC WOOD FLOOR FINISH



## SPECIFICATIONS:

VOC ..... 350 g/L  
 Solids ..... 56% - 58%  
 Flash Point ..... > 101°F (> 38°C)  
 Solvent ..... Mineral Spirits  
 Viscosity ..... 130 - 230 cps  
 Odor ..... Solvent Like  
 Coverage ..... 500 - 600 sq. ft/gal  
 Dry Time: ..... 6 - 7 Hours  
 Color (Wet) ..... Dark Amber  
 Color (Dry) ..... Amber Clear  
 Sheens ..... Super High Gloss, Semi-Gloss, Satin, Matte  
 Sizes ..... 1g & 5g Containers

## FEATURES

- Great Coverage & Low Odor
- Beautifies and Protects
- 350 VOC Formulation
- High Solids
- Commercial and Residential Use

## PROVEN QUALITY AND VALUE WITH CONSISTENT RESULTS

Absco Professional Polyurethane Wood Floor Finish makes it easy, with great coverage, easy application and multiple VOC formulations. Its oil-modified high solids formulation is durable, self-leveling and is formulated for beauty and protection. And this 350 VOC formula is designed for residential and commercial use.

**Please refer to the product label for specific surface preparation and application instructions.**



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings,  
visit [canlakcoatings.com](http://canlakcoatings.com) or call us at **800-432-4333**.