

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 1 of 20

**Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)**



## SECTION 1: Identification

### Product Identifier

**Product Name:** Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

### Recommended Use of the Product and Restriction on Use

**Relevant Identified Uses:** Not determined or not applicable.

**Uses Advised Against:** Not determined or not applicable.

**Reasons Why Uses Advised Against:** Not determined or not applicable.

### Manufacturer or Supplier Details

#### Manufacturer:

#### United States

Canlak Coatings  
1999 Elizabeth Street  
North Brunswick, New Jersey 089026316  
(732)821-3200  
<https://canlakcoatings.com>

### Emergency Telephone Number:

#### United States

CHEMTREC  
(703)527-3887 (24 HRS)  
(800)424-9300

## SECTION 2: Hazard(s) Identification

### GHS Classification:

Flammable liquids, category 3  
Eye irritation, category 2A  
Skin sensitization, category 1  
Germ cell mutagenicity, category 1B  
Carcinogenicity, category 1B  
Reproductive toxicity, category 2

### Label elements

#### Hazard Pictograms:



**Signal Word:** Danger

### Hazard statements:

H226 Flammable liquid and vapor  
H319 Causes serious eye irritation  
H317 May cause an allergic skin reaction  
H340 May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).  
H350 May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 2 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

H361 Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

### Precautionary Statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P280 Wear protective gloves/protective clothing/eye protection/face protection

P264 Wash skin thoroughly after handling

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use ... to extinguish

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention

P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P321 Specific treatment (see ... on this label)

P363 Wash contaminated clothing before reuse

P308+P313 IF exposed or concerned: Get medical advice/attention

P403+P235 Store in a well-ventilated place. Keep cool

P405 Store locked up

P501 Dispose of contents/container to...

**Hazards Not Otherwise Classified:** None

## SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 64742-47-8	Distillates (petroleum), hydrotreated light	<55
CAS Number: 8052-42-4	Asphalt	<12
CAS Number: 8052-41-3	Stoddard Solvent with < 0.1% Benzene content	<10
CAS Number: 64742-16-1	Petroleum resins	<10
CAS Number: 12002-43-6	Gilsonite	<6
CAS Number: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	<2

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 3 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

CAS Number: 22464-99-9	Zirconium 2-Ethylhexanoate	<1
CAS Number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<1
CAS Number: 8007-24-7	Cashew nutshell liquid	<1
CAS Number: 108-88-3	Toluene	<1
CAS Number: 96-29-7	Methyl ethyl ketoxime	<1

**Additional Information:** None

## SECTION 4: First Aid Measures

### Description of First Aid Measures

#### General Notes:

Show this Safety Data Sheet to the doctor in attendance.

#### After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

#### After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

#### After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

#### After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

### Most Important Symptoms and Effects, Both Acute and Delayed

#### Acute Symptoms and Effects:

Product is flammable. Exposure to sources of ignition may cause physical injury.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

#### Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 4 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Exposure may cause genetic defects. Effects are dependent on exposure (dose, concentration, contact time).

Exposure may cause cancer. Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

### Immediate Medical Attention and Special Treatment

#### Specific Treatment:

Skin/eye burns require immediate treatment.

#### Notes for the Doctor:

Treat symptomatically.

## SECTION 5: Firefighting Measures

### Extinguishing Media

#### Suitable Extinguishing Media:

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### Unsuitable Extinguishing Media:

Do not use water jet.

### Specific Hazards During Fire-Fighting:

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Thermal decomposition may produce irritating/toxic fumes/gases.

### Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

### Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

## SECTION 6: Accidental Release Measures

### Personal Precautions, Protective Equipment, and Emergency Procedures:

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 5 of 20

### Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

#### Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

#### Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

#### Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

### SECTION 7: Handling and Storage

#### Precautions for Safe Handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

#### Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

### SECTION 8: Exposure Controls/Personal Protection

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 6 of 20

### Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Only those substances with limit values have been included below.

#### Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 350 mg/m <sup>3</sup> (up to 10 hr [petroleum distillates, naphtha])
	Distillates (petroleum), hydrotreated light	64742-47-8	Ceiling Limit: 1800 mg/m <sup>3</sup> ([15 min] petroleum distillates, naphtha)
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 100 mg/m <sup>3</sup> (up to 10 hr [kerosene])
	Asphalt	8052-42-4	Ceiling Limit: 5 mg/m <sup>3</sup> (fumes [15 min])
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	REL-TWA: 350 mg/m <sup>3</sup> (up to 10 hr)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	IDLH: 20000 mg/m <sup>3</sup>
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	Ceiling Limit: 1800 mg/m <sup>3</sup> (15 min)
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	REL-TWA: 350 mg/m <sup>3</sup> ([up to 10 hr] for Stoddard Solvent)
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	Ceiling Limit: 1800 mg/m <sup>3</sup> ([15 min] for Stoddard Solvent)
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	IDLH: 1000 ppm
	Zirconium 2-Ethylhexanoate	22464-99-9	REL-TWA: 5 mg/m <sup>3</sup> (as Zr [for up to a 10-hour workday during a 40-hour workweek])
	Zirconium 2-Ethylhexanoate	22464-99-9	STEL: 10 mg/m <sup>3</sup> (as Zr)
	Zirconium 2-Ethylhexanoate	22464-99-9	IDLH: 25 mg/m <sup>3</sup> (as Zr)
	Cobalt bis(2-ethylhexanoate)	136-52-7	REL-TWA: 0.05 mg/m <sup>3</sup> (cobalt metal dust; cobalt metal fume; cobalt metal powder; elemental cobalt)
	Cobalt bis(2-ethylhexanoate)	136-52-7	IDLH: 20 mg/m <sup>3</sup> (cobalt metal dust; cobalt metal fume; cobalt metal powder; elemental cobalt)
	Toluene	108-88-3	REL-TWA: 375 mg/m <sup>3</sup> (100 ppm [up to 10 hr])
	Toluene	108-88-3	15-Minute STEL: 560 mg/m <sup>3</sup> (150 ppm)
	Toluene	108-88-3	IDLH: 500 ppm
OSHA	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 2000 mg/m <sup>3</sup> (500 ppm [aliphatic hydrocarbons])
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	PEL: 2900 mg/m <sup>3</sup> (500 ppm)
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	TWA: 400 mg/m <sup>3</sup> (100 ppm)
	Zirconium 2-Ethylhexanoate	22464-99-9	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (as Zr)
	Cobalt bis(2-ethylhexanoate)	136-52-7	8-Hour TWA-PEL: 0.1 mg/m <sup>3</sup> (cobalt metal dust; cobalt metal fume; cobalt metal powder; elemental cobalt)
	Toluene	108-88-3	8-Hour TWA-PEL: 200 ppm

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 7 of 20

### Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Toluene	108-88-3	Ceiling Limit: 300 ppm
	Toluene	108-88-3	Peak Exposure Limit Value: 500 ppm (for an 8 hr shift; duration: 10 minutes [Table Z-2])
United States(California)	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 1600 mg/m <sup>3</sup> (400 ppm [aliphatic hydrocarbons])
	Asphalt	8052-42-4	8-Hour TWA: 5 mg/m <sup>3</sup> (Asphalt (petroleum) fumes)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA-PEL: 525 mg/m <sup>3</sup> (100 ppm)
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	STEL: 1800 mg/m <sup>3</sup> (400 ppm)
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	8-Hour TWA-PEL: 1600 mg/m <sup>3</sup> ([400 ppm] Rubber solvent, naphtha)
	Zirconium 2-Ethylhexanoate	22464-99-9	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (as Zr)
	Zirconium 2-Ethylhexanoate	22464-99-9	15-Minute STEL: 10 mg/m <sup>3</sup> (as Zr)
	Cobalt bis(2-ethylhexanoate)	136-52-7	8-Hour TWA-PEL: 0.02 mg/m <sup>3</sup> (cobalt metal dust; cobalt metal fume; cobalt metal powder; elemental cobalt)
	Toluene	108-88-3	8-Hour TWA-PEL: 37 mg/m <sup>3</sup> (10 ppm)
	Toluene	108-88-3	15-Minute STEL: 560 mg/m <sup>3</sup> (150 ppm)
Toluene	108-88-3	Ceiling Limit: 500 ppm	
ACGIH	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA: 200 mg/m <sup>3</sup> (Kerosene and jet-fuels [non-aerosol], as total hydrocarbon vapor)
	Asphalt	8052-42-4	8-Hour TWA: 0.5 mg/m <sup>3</sup> (fume, as benzene-soluble aerosol, inhalable fraction)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	TLV-TWA: 100 ppm (8hr)
	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	8-Hour TWA: 100 ppm (for Stoddard Solvent)
	Zirconium 2-Ethylhexanoate	22464-99-9	8-Hour TWA: 5 mg/m <sup>3</sup> (as Zr [TLV-TWA])
	Zirconium 2-Ethylhexanoate	22464-99-9	15-Minute STEL: 10 mg/m <sup>3</sup> (as Zr)
	Cobalt bis(2-ethylhexanoate)	136-52-7	8-Hour TWA: 0.02 mg/m <sup>3</sup> (inhalable particulate matter) (cobalt [7440-48-4] and inorganic compounds, as Co)
	Toluene	108-88-3	8-Hour TWA: 20 ppm
WEEL	Methyl ethyl ketoxime	96-29-7	8-Hour TWA: 36 mg/m <sup>3</sup> (10 ppm)

### Biological Limit Values:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 8 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	Asphalt	8052-42-4	1-Hydroxypyrene, with hydrolysis (1-HP)	Urine	ESW	2.5 µg/l
	Toluene	108-88-3	Toluene	Blood	Prior to last shift of work week	0.02 mg/L
	Toluene	108-88-3	o-Cresol, with hydrolysis	Creatinine in urine	End of shift	0.3 mg/g
	Toluene	108-88-3	Toluene	Urine	End of shift	0.03 mg/L

### Information on Monitoring Procedures:

Not determined or not applicable.

### Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

### Personal Protection Equipment

#### Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

#### Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

#### Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

### General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

## SECTION 9: Physical and Chemical Properties

### Information on Basic Physical and Chemical Properties

Appearance	Not determined or not available.
Odor	Not determined or not available.
Odor threshold	Not determined or not available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 9 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	Not determined or not available.
<b>Flash point (closed cup)</b>	Not determined or not available.
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	Not determined or not available.
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Not determined or not available.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Not determined or not available.
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

### SECTION 10: Stability and Reactivity

#### Reactivity:

Not reactive under recommended handling and storage conditions.

#### Chemical Stability:

Stable under recommended handling and storage conditions.

#### Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

#### Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

#### Incompatible Materials:

None known.

#### Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological Information

#### Acute Toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

**Substance Data:**

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 10 of 20

### Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Name	Route	Result
Distillates (petroleum), hydrotreated light	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5.28 mg/L (4 hr [vapor])
Asphalt	oral	LD50 Rat: >5000 mg/kg
	inhalation	LC50 Rat: >94.4 mg/m <sup>3</sup> (4.5 h [mixed aerosol and vapor])
	dermal	LD50 Rabbit: >2000 mg/kg
Stoddard Solvent with < 0.1% Benzene content	oral	LD50 Rat: > 5000 mg/kg
	inhalation	LC50 Rat: > 5.5 mg/L (4 hr [vapour])
	dermal	LD50 Rabbit: > 3000 mg/kg
Petroleum resins	oral	LD50 Rat: >2000 mg/kg
Naphtha (petroleum), hydrodesulfurized heavy	oral	LD50 Rat: > 5000 mg/kg ([Read-across substance data])
	dermal	LD50 Rabbit: >2000 mg/kg ([Read-across substance data])
	inhalation	LC50 Rat: >5.6 mg/L (4 hr [Vapour, Read-across substance data])
Zirconium 2-Ethylhexanoate	oral	LD50 Rat: > 2000 mg/kg
	dermal	LD50 Rat: > 2000 mg/kg
	inhalation	LC50 Rat: > 4.3 mg/L (4 hr [aerosol])
Cobalt bis(2-ethylhexanoate)	oral	LD50 Rat: 3129 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
Cashew nutshell liquid	dermal	LD50 Rat: 1100 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg
Toluene	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >5000 mg/kg
	inhalation	LC50 Rat: 25.7 mg/L (4 hr [Vapour])
Methyl ethyl ketoxime	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 100 mg/kg
	inhalation	LC50 Rat: > 4.83 mg/L (4 hr [vapour])

#### Skin Corrosion/Irritation

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**

No data available.

**Substance Data:**

Name	Result
Distillates (petroleum), hydrotreated light	Causes skin irritation.
Stoddard Solvent with < 0.1% Benzene content	Causes skin irritation.
Cashew nutshell liquid	Causes skin irritation
Toluene	Causes skin irritation.
Methyl ethyl ketoxime	Causes skin irritation.

#### Serious Eye Damage/Irritation

**Assessment:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 11 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Causes serious eye irritation.

### Product Data:

No data available.

### Substance Data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes serious eye irritation.
Cobalt bis(2-ethylhexanoate)	Causes serious eye irritation.
Cashew nutshell liquid	Causes serious eye damage
Methyl ethyl ketoxime	Causes serious eye damage.

### Respiratory or Skin Sensitization

#### Assessment:

May cause an allergic skin reaction.

#### Product Data:

No data available.

#### Substance Data:

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause an allergic skin reaction.
Cashew nutshell liquid	May cause an allergic skin reaction.
Methyl ethyl ketoxime	May cause an allergic skin reaction.

### Carcinogenicity

#### Assessment:

May cause cancer.

**Product Data:** No data available.

#### Substance Data:

Name	Species	Result
Asphalt	Not Applicable	There is inadequate evidence that bitumens alone are carcinogenic to humans. There is sufficient evidence for the carcinogenicity of extracts of steam-refined bitumens, air-refined bitumens and pooled mixtures of steam- and air-refined bitumens in experimental animals.
Naphtha (petroleum), hydrodesulfurized heavy		May cause cancer.
Methyl ethyl ketoxime		May cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Distillates (petroleum), hydrotreated light	Not Applicable
Asphalt	Group 2B
Stoddard Solvent with < 0.1% Benzene content	Not Applicable
Petroleum resins	Not Applicable
Gilsonite	Not Applicable
Naphtha (petroleum), hydrodesulfurized heavy	Group 3

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 12 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Name	Classification
Zirconium 2-Ethylhexanoate	Not Applicable
Cobalt bis(2-ethylhexanoate)	Group 2B
Cashew nutshell liquid	Not Applicable
Toluene	Group 3
Methyl ethyl ketoxime	Not Applicable

### National Toxicology Program (NTP):

Name	Classification
Distillates (petroleum), hydrotreated light	Not Applicable
Asphalt	Not Applicable
Stoddard Solvent with < 0.1% Benzene content	Not Applicable
Petroleum resins	Not Applicable
Gilsonite	Not Applicable
Naphtha (petroleum), hydrodesulfurized heavy	Not Applicable
Zirconium 2-Ethylhexanoate	Not Applicable
Cobalt bis(2-ethylhexanoate)	Reasonably anticipated to be human carcinogens
Cashew nutshell liquid	Not Applicable
Toluene	Not Applicable
Methyl ethyl ketoxime	Not Applicable

**OSHA Carcinogens:** Not applicable

### Germ Cell Mutagenicity

**Assessment:**

May cause genetic defects.

**Product Data:**

No data available.

**Substance Data:**

Name	Result
Naphtha (petroleum), hydrodesulfurized heavy	May cause genetic defects.

### Reproductive Toxicity

**Assessment:**

Suspected of damaging fertility or the unborn child.

**Product Data:**

No data available.

**Substance Data:**

Name	Result
Zirconium 2-Ethylhexanoate	Suspected of damaging the unborn child (developmental toxicity) via oral exposure.
Cobalt bis(2-ethylhexanoate)	May damage fertility. May damage the unborn child.
Toluene	Suspected of damaging the unborn child .

### Specific Target Organ Toxicity (Single Exposure)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 13 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**

No data available.

**Substance Data:**

Name	Result
Distillates (petroleum), hydrotreated light	May cause drowsiness or dizziness.
Toluene	May cause drowsiness or dizziness.
Methyl ethyl ketoxime	May cause drowsiness or dizziness. Causes damage to the respiratory tract.

### Specific Target Organ Toxicity (Repeated Exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**

No data available.

**Substance Data:**

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes damage to the Central Nervous System through prolonged or repeated exposure via inhalation.
Naphtha (petroleum), hydrodesulfurized heavy	Causes damage to the central nervous system through prolonged or repeated exposure.
Toluene	May cause damage to organs (central nervous system; kidneys; liver) through prolonged or repeated exposure. Exposure to the substance may increase noise-induced hearing loss and adversely affect color vision.
Methyl ethyl ketoxime	May cause damage to the blood system through prolonged or repeated exposure.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**

No data available.

**Substance Data:**

Name	Result
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.
Stoddard Solvent with < 0.1% Benzene content	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrodesulfurized heavy	May be fatal if swallowed and enters airways.
Toluene	May be fatal if swallowed and enters airways.

### Information on Likely Routes of Exposure:

No data available.

### Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

### Other Information:

No data available.

## SECTION 12: Ecological Information

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 14 of 20

### Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

#### Acute (Short-Term) Toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

#### Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Fish LC50 Oncorhynchus mykiss: 2 - 5 mg/L (96 hr [LL50; mortality])
	Aquatic Invertebrates EC50 Daphnia magna: 1.4 mg/L (48 hr [EL50; mobility])
	Aquatic Plants EC50 Raphidocelis subcapitata: 1 - 3 mg/L (72 hr [EL50; cell number])
Asphalt	Aquatic Plants EC50 Freshwater algae: >1000 mg/L (72 hr [growth rate; read-across])
Stoddard Solvent with < 0.1% Benzene content	Fish LC50 Oncorhynchus mykiss: 2.5 mg/L (96 hr)
	Aquatic Invertebrates LC50 Daphnid: 0.107 mg/L (48 hr [QSAR])
	Aquatic Plants EC50 Green algae: 0.277 mg/L (96 hr [QSAR])
Petroleum resins	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodemus subspicatus: > 100 mg/L (72 hr [Growth rate & Yield])
Naphtha (petroleum), hydrodesulfurized heavy	Aquatic Plants EC50 Raphidocelis subcapitata: 3.1 mg/L (72 hr [growth rate-Read-across substance data])
	Aquatic Invertebrates EC50 Daphnia magna: 4.5 mg/L (48 hr [EL50-mobility, Read-across substance data])
	Fish LC50 Pimephales promelas: 8.2 mg/L (96 hr [LL50- Read-across substance data])
Zirconium 2-Ethylhexanoate	Fish LC50 Oncorhynchus mykiss: > 100 mg/L (96 hr [read-across substance])
	Aquatic Invertebrates EC50 Daphnia magna: > 0.17 mg/L (48 hr [mortality])
	Aquatic Plants EC50 Raphidocelis subcapitata: 500 mg/L (72 hr [growth rate; read-across substance data])
Cobalt bis(2-ethylhexanoate)	Fish LC50 Pimephales promelas: 1.512 mg/L (96 hr [Read-across substance data])
	Aquatic Invertebrates EC50 Daphnia magna: 5.89 mg/L (48 hr [mobility, Read-across substance data])
	Aquatic Plants EC50 Raphidocelis subcapitata: 0.144 mg/L (72 hr [growth rate, Read-across substance data])
Toluene	Fish LC50 Oncorhynchus kisutch: 5.5 mg/L (96 hr)
	Aquatic Invertebrates EC50 Ceriodaphnia dubia: 3.78 mg/L (48 hr [mortality])
Methyl ethyl ketoxime	Fish LC50 Oryzias latipes: > 100 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 201 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Scenedesmus capricornutum: 11.8 mg/L (72 hr [growth rate])

#### Chronic (Long-Term) Toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

#### Substance Data:

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 15 of 20

### Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Name	Result
Distillates (petroleum), hydrotreated light	Fish NOEC Oncorhynchus mykiss: 0.098 mg/L (28 d [NOEL; mortality])
	Aquatic Invertebrates NOEC Daphnia magna: 0.89 mg/L (21 d [EL50; reproduction])
Stoddard Solvent with < 0.1% Benzene content	Fish NOEC Oncorhynchus mykiss: 0.02 mg/L (30d [QSAR])
	Aquatic Invertebrates NOEC Daphnia magna: 0.1 mg/L (21d [reproduction])
	Aquatic Plants NOEC Green algae: 0.142 mg/L (30d [QSAR])
Naphtha (petroleum), hydrodesulfurized heavy	Aquatic Invertebrates NOEC Daphnia magna: 2.6 mg/L (21 d [NOELR-reproduction, Read-across substance data])
	Fish NOEC Pimephales promelas: 2.6 mg/L (14 d [NOELR-mortality, Read-across substance data])
Zirconium 2-Ethylhexanoate	Aquatic Invertebrates NOEC Daphnia magna: 18 mg/L (21 d [reproduction])
	Aquatic Plants NOEC Raphidocelis subcapitata: 130 mg/L (72 hr [growth rate; read-across substance data])
Cobalt bis(2-ethylhexanoate)	Fish NOEC Pimephales promelas: 0.21 mg/L (34 d [mortality, Read-across substance data])
	Aquatic Invertebrates NOEC Daphnia magna: 0.0608 mg/L (21 d [reproduction, Read-across substance data])
	Aquatic Plants NOEC Lemna minor: 0.00892 mg/L (7 d [growth rate])
Toluene	Aquatic Invertebrates NOEC Ceriodaphnia dubia: 0.74 mg/L (7 d [reproduction])
	Aquatic Plants NOEC Skeletonema costatum: 10 mg/L (72 hr [cell number])
Methyl ethyl ketoxime	Fish NOEC Oryzias latipes: 50 mg/L (14 d)
	Aquatic Invertebrates NOEC Daphnia magna: >= 100 mg/L (21 d)
	Aquatic Plants NOEC Scenedesmus capricornutum: 2.56 mg/L (72 hr [growth rate])

### Persistence and Degradability

**Product Data:** No data available.

#### Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	The substance is not readily biodegradable. 58.6% degradation in water, after 28 days.
Asphalt	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
Stoddard Solvent with < 0.1% Benzene content	The substance is readily biodegradable. >63% degradation, measured by CO2 evolution, after 28 days.
Petroleum resins	The substance is not readily biodegradable. 18% degradation measured by CO2 evolution after 28 days.
Naphtha (petroleum), hydrodesulfurized heavy	Standard biodegradability studies are not applicable to UVCB substances.
Zirconium 2-Ethylhexanoate	The substance is readily biodegradable. 73.82% degradation in water, measured by CO2 evolution, after 28 days.
Cobalt bis(2-ethylhexanoate)	The substance is readily biodegradable. 60% degradation in water, measured by CO2 evolution, after 10 days.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 16 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Name	Result
Toluene	The substance is readily biodegradable. 86% degradation in water, measured by BOD/ThOD, after 20 days.
Methyl ethyl ketoxime	The substance is inherently biodegradable in water. 70% degradation in water, measured by DOC removal, after 18 days.

### Bioaccumulative Potential

**Product Data:** No data available.

#### Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Standard bioaccumulation studies are not applicable to petroleum UVCB substances.
Asphalt	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
Stoddard Solvent with < 0.1% Benzene content	The substance is not expected to bioaccumulate. BCF (aquatic species): 39.66 L/Kg [QSAR].
Naphtha (petroleum), hydrodesulfurized heavy	Standard bioaccumulation studies are not applicable to UVCB substances.
Zirconium 2-Ethylhexanoate	The substance is not expected to bioaccumulate BCF (aquatic species): 0.064 L/kg ww
Cobalt bis(2-ethylhexanoate)	Bioaccumulation assessment using a classic BCF assessment is not considered relevant for inorganic compounds such as this substance.
Toluene	The substance is not expected to bioaccumulate (BCF: 90).
Methyl ethyl ketoxime	The substance is not expected to bioaccumulate. BCF (aquatic species): <2.5 - 5.8 dimensionless

### Mobility in Soil

**Product Data:** No data available.

#### Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Standard adsorption/desorption studies are not applicable to petroleum UVCB substances.
Asphalt	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
Stoddard Solvent with < 0.1% Benzene content	The substance is slightly mobile with a high potential for adsorption to soil and sediment [Koc at 20°C: 1451].
Naphtha (petroleum), hydrodesulfurized heavy	Standard adsorption/desorption studies are not applicable to UVCB substances.
Zirconium 2-Ethylhexanoate	The substance is mobile, therefore, there is low potential for adsorption to soil and sediment (Log Koc: 140.87).
Cobalt bis(2-ethylhexanoate)	Mobility in soil assessment based on KOC/Kd values are not relevant for inorganic compounds such as this substance.
Toluene	The substance is moderately mobile, therefore, there is moderate potential for adsorption to soil and Sediment (Koc: 205) [calculation].
Methyl ethyl ketoxime	The substance is highly mobile, therefore, adsorption to soil and sediment is not expected [Koc at 25°C: 3.519 L/kg].

### Results of PBT and vPvB assessment

**Product Data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 17 of 20

## Abcco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

### Substance Data:

#### PBT assessment:

Distillates (petroleum), hydrotreated light	The substance is a UVCB and does not contain constituents included in the SVHC candidate list as PBT at concentrations above 0.1%.
Asphalt	The substance is not PBT.
Stoddard Solvent with < 0.1% Benzene content	The substance is not PBT.
Naphtha (petroleum), hydrodesulfurized heavy	Standard PBT studies are not applicable to UVCB substances.
Zirconium 2-Ethylhexanoate	The substance is inorganic, PBT assessment does not apply.
Cobalt bis(2-ethylhexanoate)	PBT assessment does not apply to inorganic compounds such as this substance.
Toluene	The substance is not PBT.
Methyl ethyl ketoxime	The substance is not PBT.

#### vPvB assessment:

Distillates (petroleum), hydrotreated light	The substance is a UVCB and does not contain constituents included in the SVHC candidate list as vPvB at concentrations above 0.1%.
Asphalt	The substance is not vPvB.
Stoddard Solvent with < 0.1% Benzene content	The substance is not vPvB.
Naphtha (petroleum), hydrodesulfurized heavy	Standard vBvB studies are not applicable to UVCB substances.
Zirconium 2-Ethylhexanoate	The substance is inorganic, vPvB assessment does not apply.
Cobalt bis(2-ethylhexanoate)	vPvB assessment does not apply to inorganic compounds such as this substance.
Toluene	The substance is not vPvB.
Methyl ethyl ketoxime	The substance is not vPvB.

**Other Adverse Effects:** No data available.

## SECTION 13: Disposal Considerations

### Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

### Contaminated packages:

Not determined or not applicable.

## SECTION 14: Transport Information

### United States Transportation of Dangerous Goods (49 CFR DOT)

<b>UN Number</b>	Not regulated
<b>UN Proper Shipping Name</b>	Not regulated
<b>UN Transport Hazard Class(es)</b>	None
<b>Packing Group</b>	None
<b>Environmental Hazards</b>	None

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 18 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

Special Precautions for User	None
------------------------------	------

### International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

## SECTION 15: Regulatory Information

### United States Regulations

#### Inventory Listing (TSCA):

64742-47-8	Distillates (petroleum), hydrotreated light	Listed - Active
8052-42-4	Asphalt	Listed - Active
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed - Active
64742-16-1	Petroleum resins	Listed - Active
12002-43-6	Gilsonite	Not Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed - Active
22464-99-9	Zirconium 2-Ethylhexanoate	Listed - Active
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed - Active
8007-24-7	Cashew nutshell liquid	Listed - Active
108-88-3	Toluene	Listed - Active
96-29-7	Methyl ethyl ketoxime	Listed - Active

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 19 of 20

**Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)**

**SARA Section 302 Extremely Hazardous Substances:** None of the ingredients are listed.

**SARA Section 313 Toxic Chemicals:**

136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
108-88-3	Toluene	Listed

**CERCLA:**

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	100 lbs for RCRA D001
8052-42-4	Asphalt	Listed	100 lbs for RCRA D001
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed	100 lbs for RCRA D001
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed	100 Lbs. for RCRA D001
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed	
108-88-3	Toluene	Listed	1000 lbs

**RCRA:**

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	D001
8052-42-4	Asphalt	Listed	D001
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed	D001
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed	D001
108-88-3	Toluene	Listed	U220

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

**Massachusetts Right to Know:**

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
8052-42-4	Asphalt	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed
108-88-3	Toluene	Listed

**New Jersey Right to Know:**

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
8052-42-4	Asphalt	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
108-88-3	Toluene	Listed

**New York Right to Know:**

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
8052-42-4	Asphalt	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.04.2026

Page 20 of 20

## Absco Quick Dry Penetrating Wood Finish- Gunstock (30951, 30954)

108-88-3	Toluene	Listed
----------	---------	--------

### Pennsylvania Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed
8052-42-4	Asphalt	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
108-88-3	Toluene	Listed

### California Proposition 65:

**⚠ WARNING:** This product can expose you to Bitumens, extracts of steam-refined and air refined; which is known to the State of California to cause cancer; and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Additional information:** Not determined.

## SECTION 16: Other Information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 0-0-0

**HMIS:** 0-0-0

**Initial Preparation Date:** 03.04.2026

**End of Safety Data Sheet**