



POLYURETHANE 275 VOC FLOOR FINISH

FROM THE MAKER

PRO
SELECT
POLYURETHANE FLOOR FINISH



SPECIFICATIONS:

VOC.....	<275 g/L
Solids.....	39% - 41%
Flash Point.....	> 101°F (> 38°C)
Solvent	Mineral Spirits
Viscosity.....	80 - 180 cps
Odor.....	Solvent Like
Coverage.....	500 sq. ft/gal
Dry Time:.....	4 - 8 Hours
Color (Wet).....	Slightly Milky
Color (Dry).....	Amber Clear
Sheens.....	Super High Gloss, Semi-Gloss, Satin, Matte
Sizes	1g & 5g Containers

FEATURES

- Great Coverage & Low Odor
- Beautifies and Protects
- 275 VOC Formulation is Compliant Nationally
- High Solids
- Commercial and Residential Use

PROVEN QUALITY AND VALUE WITH CONSISTENT RESULTS IN A NATIONALLY VOC COMPLIANT FORMULA

PRO SELECT Professional Polyurethane Wood Floor Finish makes it easy, with great coverage and easy application. Its oil-modified high solids formulation is durable, self-leveling and is formulated for beauty and protection. And this 275 VOC formula is compliant nationally. It is designed for residential and commercial use.

Please refer to the product label for specific surface preparation and application instructions.



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit canlakcoatings.com or call us at **800-432-4333**.